

## E-VISION LASER 5100 DIGITAL PROJECTOR



THE VISIONARIES CHOICE

**4,500 ANSI / 5,100 ISO Lumens | Contrast Ratio: 2,000:1 Native 20,000:1 Dynamic | Part Number: 120-552**

### Colour System:

Laser Phosphor

### DMD Specification:

1920 x 1200 pixels native resolution.

Fast transit pixels for smooth greyscale and improved contrast.

### Display Type:

1 x 0.67" DarkChip™ DMD™

### Aspect Ratio:

16x10

Fill Factor

## Key Features

### Video & Graphics Processing

- HDMI 1.4a for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.
- Synchronisation of active 3D glasses.
- DICOM simulation mode.
- Mobile High-Definition Link (MHL™) connection allows mirrored content from smartphones, tablets and other portable consumer electronics devices.

### Geometry Correction

- Vertical & Horizontal Keystone correction (2D: Vertical  $\pm 15^\circ$ , Horizontal  $\pm 15^\circ$ ).
- Four Corner adjustment.
- Selectable 16:9, 4:3, Native, Letterbox and Full Screen aspect ratios.
- Digital Zoom +10~-10.

### HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® includes audio, Ethernet 100BaseT and RS232/IR control.


## Colour Processing

- 2 x speed, 3 Segment (GBY) Phosphor wheel.
- 2 x 120Hz speed, 4 Segment (RGBY) Colour wheel.
- 10-bit colour display.
- Powerful seven point colour correction for accurate colour matching.

## Source Compatibility:

Graphics standards up to 1920 x 1200 resolution at 60Hz.  
Input support for 4K-UHD, 3840 x 2160 and 4096 x 2160 at 60 Hz.

## Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.4a	HDMI	2	LAN	RJ45	1
HDMI 1.4a + MHL	HDMI	1	RS-232C	9-pin D-sub	1
VGA / Analog RGB	15-pin D-Sub	1	USB (for Service)	Mini B	1
VGA / Monitor Out	15-pin D-Sub	1	3D Sync Out	VESA 3-PIN mini DIN	1
Composite Video	RCA	1			
HDBaseT	RJ45	1	<b>NOTE: The HDBaseT and LAN ports are not shared.</b>		
USB Type A / (5V/1.5A)	USB Type A	1			
<b>NOTE: The USB is to power WHDI™ interfaces.</b>					
<b>Audio:</b>					
Audio IN L+R	Phono	2			
Audio IN L+R	3.5 mm jack	1			
Mic IN	3.5 mm jack	1			
Audio OUT (variable)	3.5 mm jack	1			
Speakers	5W speaker	2			
<b>3D Formats Supported</b>			<b>HDTV Formats Supported</b>		
Frame Packing			1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)		
Frame Sequential					
Side By Side (half)					
Top and Bottom					
<b>Computer Compatibility</b>			<b>Bandwidth</b>		
VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz					
<b>Remote Control</b>			<b>Automation Control</b>		
IR remote control, 2 x IR receivers (front sensitivity up to 7m, rear sensitivity up to 10m)			LAN control - Crestron RoomView® Connected		
			LAN control - Crestron eControl		
			LAN control - Extron		
			LAN control - AMX SSDP		
			LAN control to RS232 by Telnet		
			HDBaseT communication		
			Projector status email alerts		
			PJ Link (Class1)		
<b>Colour Temperature</b>			<b>Operation</b>		
Warm / Normal / Cold					
<b>Illumination Type</b>			<b>Typical illumination Life</b>		
Laser Light Source			20,000 hours		
<b>Lenses</b>					
<b>Lens</b>	<b>Part No.</b>	<b>Optimised Focus Range*</b>	<b>Lens Shift</b>		
0.5 :1	N/A	0.76m - 3.23m	Vert: Fixed Offset 0.6 (U) frame		

\* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,

## Lens Mount

Manual focus

### Mechanical Mounting

Front/Rear  
 Front/Rear Ceiling  
 Two adjustable front feet, 10° (43mm)  
 Ceiling Mount compatible chassis with 7 off M4 mounting holes

### Orientation

**Table Top or Inverted:** Yes  
**Pointing Up:** Yes  
**Pointing Down:** Yes  
**Roll (Portrait):** Yes

### Power Requirements

100-240VAC 50/60Hz single phase

### Power Consumption

Normal Mode (100%) 480W @230V 500W @110V  
 Eco Mode (80%) 355W @230V 365W @110V

### Thermal Dissipation

Normal Mode (typical):  
 1706 BTU/Hour @ 110VAC  
 1638 BTU/Hour @ 230VAC

### Fan Noise

Normal Mode Typ: 36 dBA / Max: 38 dBA

### Operating/Storage Temperature

Operating: 0° to 40°C (32F to 104F)  
 Storage: -20° to 60°C (-4F to 140F)

### Operating Humidity

10 to 85% non-condensing

### Weight (Chassis Only)

10.5 kg  
 23.21 lb

### Dimensions

L: 43.71 cm W: 36.0 cm H: 17.71 cm  
 L: 17.2 in W: 14.17 in H: 6.97 in

### Safety & EMC Regulations

UL/cUL, CB, CCC/CECP, FCC Class B, FDA, CE  
 IEC 60825-1:2007 3R  
 IEC60825-1:2014 Class 1  
 IEC EN 62471-5 Risk Group 2

### Accessories

#### Accessory

Infrared Remote (replacement)

#### Part No.

117-880

*\*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

### Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[User Guides \(German\)](#)

[STEP / IGS Drawings](#)

[User Guides \(French\)](#)

[Laser Risk Group Document](#)

[Important Information](#)

[Control Protocol](#)



Certificate Number 13629  
 ISO 9001



**DIGITAL PROJECTION, LTD** GREENSIDE WAY, MIDDLETON  
MANCHESTER, UK. M24 1XX  
T: +44.161.947.3300 | F: +44.161.684.7674 | [www.digitalprojection.co.uk](http://www.digitalprojection.co.uk)

**DIGITAL PROJECTION, INC** 55 CHASTAIN ROAD, SUITE 115 KENNESAW,  
GA. 30144  
T: 770.420.1350 } F: 770.420.1360 | [www.digitalprojection.com](http://www.digitalprojection.com)

**DIGITAL PROJECTION, CHINA** Rm A2301, Shaoyaoju 101 North Lane, Shi  
Ao International Center, Chaoyang District, Beijing 100029, PR China  
T: +86.10.58239771 | F: +86 10 58239770