

[Click to Print This Page](#)



M-VISION LASER 18K DIGITAL PROJECTOR

THE VISIONARIES CHOICE



M-Vision Laser 18K WUXGA

16,000 ANSI / 18,000 ISO Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) | Part Number: 120-605

Key Specifications:

| | |
|---------------------------|---|
| Colour System: | Blue Laser Phosphor + 4-segment colour wheel |
| Display Type: | 1 x 0.96" DarkChip™ DMD™ |
| DMD Specification: | 1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast. |
| Aspect Ratio: | 16x10 |
| Fill Factor | 87% |
| Key Features: | <p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & TopBottom 3D Formats.• Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources.• Dual Pipe Processing: Two sources in parallel for Left and Right eyes.• Synchronisation of active glasses.• 3G-SDI with loop-through.• 24p and 1080p native display. <p>Geometry Correction</p> <ul style="list-style-type: none">• Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.• Blanking control for custom input window sizing.• Scaling for fixed aspect ratio screens. <p>Edge Blending</p> |

- Correction for non-active pixels at the edge of the display.

Picture in Picture

- Two sources can be displayed either one within the other (PIP) , or side by side, with the original aspect ratios maintained.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from source with low cost cabling.

Colour Processing

- Powerful seven-point colour correction for accurate colour matching.

Projector Controller Software

- Intuitive user interface for network control.
- Simultaneous control of user-defined groups of projectors.
- At-a-glance monitoring of projector status.

Projector Automation

- Real-time clock provides daily on/off automation.

Installation

- Integrated stacking mount pins.
- Eye bolts included for easy rigging.

Source Compatibility


3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.
 HDMI including Deep Color™ processing.
 Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI or DisplayPort.

Inputs/Outputs

| Video & Computer | | |
|--|-------------------|-----|
| Type | Connector | Qty |
| DisplayPort 1.1a | DisplayPort | 2 |
| HDMI 1.4a | HDMI | 2 |
| 3G-SDI in | BNC | 1 |
| 3G-SDI out | BNC | 1 |
| HDBaseT (see LAN) | LAN RJ45 | 1 |
| Communication & Control | | |
| Type | Connector | Qty |
| 3D Sync Out | BNC | 1 |
| 3D Sync In | BNC | 1 |
| LAN | RJ45 | 1 |
| RS232 | RJ45 | 1 |
| Wired Remote | 9-pin D-Sub | 1 |
| 12V Trigger | 3.5mm Stereo Jack | 1 |
| | 3.5mm Stereo Jack | 2 |
| NOTE: The HDBaseT and LAN ports are not shared. | | |

3D Formats Supported

Frame Packing
 Dual Pipe

| | Frame Sequential Side By Side (half) Top and Bottom | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------------|--|------------------------|---|------------------------|--------------------|--------------------|---------|----------------|---|----------------------|---------|------------|---|----------------------|---------|------------|---|----------------------|---------|--------------|---|----------------------|---------|----------|---|
| HDTV Formats Supported | 1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50Hz, 60Hz) | | | | | | | | | | | | | | | | | | | | | | | | |
| Computer Compatibility | Up to 1920 x 1200 | | | | | | | | | | | | | | | | | | | | | | | | |
| Bandwidth | 165 MHz on analog RGB 165 Megapixels per second on HDMI | | | | | | | | | | | | | | | | | | | | | | | | |
| Remote Control | Addressable IR Remote Control, wireless and wired On-Board keypad | | | | | | | | | | | | | | | | | | | | | | | | |
| Automation Control | Crestron RoomView® Connected PJLink Class 1 LAN RS232 AMX (Device Discovery) Served web page | | | | | | | | | | | | | | | | | | | | | | | | |
| Colour Temperature | 3200K to 9300K | | | | | | | | | | | | | | | | | | | | | | | | |
| Operation |  | | | | | | | | | | | | | | | | | | | | | | | | |
| illumination Type | Laser Light Source | | | | | | | | | | | | | | | | | | | | | | | | |
| Typical illumination Life | 20,000 hours | | | | | | | | | | | | | | | | | | | | | | | | |
| Lenses | <table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.9 - 1.2 : 1 zoom</td> <td>120-624</td> <td>0.92m - 13.46m</td> <td>Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.15 (L) 0.15 (R) frame</td> </tr> <tr> <td>1.20 - 1.56 : 1 zoom</td> <td>120-625</td> <td>1m - 17.5m</td> <td>Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame</td> </tr> <tr> <td>1.50 - 2.00 : 1 zoom</td> <td>120-626</td> <td>2m - 21.8m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame</td> </tr> <tr> <td>2.00 - 4.00 : 1 zoom</td> <td>120-627</td> <td>2.5m - 41.8m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame</td> </tr> <tr> <td>4.00 - 7.00 : 1 zoom</td> <td>120-628</td> <td>4m - 42m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame</td> </tr> </tbody> </table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p> | Lens | Part No. | Optimised Focus Range* | Lens Shift (Frame) | 0.9 - 1.2 : 1 zoom | 120-624 | 0.92m - 13.46m | Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | 1.20 - 1.56 : 1 zoom | 120-625 | 1m - 17.5m | Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | 1.50 - 2.00 : 1 zoom | 120-626 | 2m - 21.8m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | 2.00 - 4.00 : 1 zoom | 120-627 | 2.5m - 41.8m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | 4.00 - 7.00 : 1 zoom | 120-628 | 4m - 42m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame |
| Lens | Part No. | Optimised Focus Range* | Lens Shift (Frame) | | | | | | | | | | | | | | | | | | | | | | |
| 0.9 - 1.2 : 1 zoom | 120-624 | 0.92m - 13.46m | Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | | | | | | | | | | | | | | | | | | | | | | |
| 1.20 - 1.56 : 1 zoom | 120-625 | 1m - 17.5m | Vert: 0.5 (U) 0.5 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | | | | | | | | | | | | | | | | | | | | | | |
| 1.50 - 2.00 : 1 zoom | 120-626 | 2m - 21.8m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | | | | | | | | | | | | | | | | | | | | | | |
| 2.00 - 4.00 : 1 zoom | 120-627 | 2.5m - 41.8m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | | | | | | | | | | | | | | | | | | | | | | |
| 4.00 - 7.00 : 1 zoom | 120-628 | 4m - 42m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.15 (L) 0.15 (R) frame | | | | | | | | | | | | | | | | | | | | | | |
| Lens Mount | Motorised shift, zoom and focus, with programmable shift | | | | | | | | | | | | | | | | | | | | | | | | |
| Mechanical Mounting | Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet | | | | | | | | | | | | | | | | | | | | | | | | |
| Orientation | Table Top or Inverted: Yes | | | | | | | | | | | | | | | | | | | | | | | | |

| | Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes | | | | |
|---|---|-----------|----------|-------------------------------|---------|
| Power Requirements | 100 - 240VAC 50/60Hz single phase * Note that in 120V operation, the projector will be at 65% brightness | | | | |
| Power Consumption | Typical 2000W @ 240VAC in Normal mode Typical 1200W @ 240VAC in ECO mode Typical 1200W @ 110VAC in Normal mode Typical 1000W @ 110VAC in ECO mode | | | | |
| Thermal Dissipation | Typical 6482 BTU/Hour @ 220VAC in Normal mode Typical 3753 BTU/Hour @ 110VAC in Normal mode | | | | |
| Fan Noise | Normal mode: 45 dBA max, 42 dBA typical Eco mode: 42 dBA max, 39dBA typical | | | | |
| Operating/Storage Temperature Operating: | Operating: 0 to 40C (32 to 104F) Storage: -20 to 60C (-4 to 140F) | | | | |
| Operating Humidity | 10% to 90% relative, non-condensing | | | | |
| Weight | 49 kg / 108 lbs | | | | |
| Dimensions | H: 24.8 cm W: 53.0 cm L: 69.5 cm H: 9.8 in W: 20.9 in L: 27.4 in | | | | |
| Safety & EMC Regulations | UL/cUL, CB, CCC, FCC Class A , CE, RoHS 2 IEC EN 60825-1:2014 Class 1 Laser Product IEC 60825-1:2007 Class 3R Laser Product IEC EN 62471-5:2015 Risk Group 3 | | | | |
| Accessories | <table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td>Infrared Remote (replacement)</td> <td>117-780</td> </tr> </tbody> </table> <p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p> | Accessory | Part No. | Infrared Remote (replacement) | 117-780 |
| Accessory | Part No. | | | | |
| Infrared Remote (replacement) | 117-780 | | | | |
| Downloads | PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings Lens CAD Drawings | | | | |
| User Guide | User Guides User Guides (Korean) Laser Risk Group Document Important Information Control Protocol | | | | |



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770



Specifications subject to change without notice.
©2022 Digital Projection. DLP®, Digital Light
Processing™ and DMD are trademarks of Texas
Instruments, Inc



Certificate Number 13629
ISO 9001