

[Click to Print This Page](#)



E-VISION 15000i 4K+

THE VISIONARIES CHOICE



E-Vision 15000i 4K+ (Preliminary)

15,000 ISO / 13,500 ANSI Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part Number: 124-369

Key Specifications:

Colour System:	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 8 Segment RGBYRGBY 2 x 7200rpm (120Hz)
Display Type:	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
DMD Specification:	1920 x 1200 pixels native display. (3840 x 2400 via 4-way pixel shift technology) Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	Video & Graphics Processing • Nexus electronics platform • Support 3840 x 2160 display resolution • HDMI 2.0 • DisplayPort 1.2 • 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours • Hue, Saturation and Gain colour management. • 24p and 1080p native display. • HDR support • Input source automatically detected • Selectable Dynamic Black

	• DICOM simulation mode • Optics engine sealed to IP6X Geometry Correction • Vertical & Horizontal Keystone correction • Four Corner adjustment • Rotation -100 to +100 with +/- 0.25° per step • Selectable aspect ratios: 5:4 / 4:3 / 16:10 /16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled • Digital Zoom 0% ~ 100% • Blanking control for custom input window sizing. • Scaling for fixed aspect ratio screens.16:10 / 16:9 / 4:3 / 2.35:1 • Custom warp Edge Blending • Correction for non-active pixels at the edge of the display. HDBaseT® Interface • Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable. • Allows the projector to be placed up to 100m from the source with low cost cabling. • HDBaseT® Includes Ethernet 100BaseT and RS232/IR control. Colour Processing • Powerful seven point colour correction for accurate colour matching. Projector LAN Control • Free Digital Projection Projector Controller II software • Intuitive user interface for network control. • At-a-glance monitoring of projector status. • Simultaneous control of user-defined groups of projectors.															
Source Compatibility	12G-SDI, Supports a high data transfer rate of up to 12 gigabits per second (Gbps), enabling the transmission of uncompressed 4K UHD (Ultra High Definition) video signals with a single connector Graphics standards up to WUXGA 1920 x 1200 - 120Hz RB, Up to WQXGA 2560 x 1600 60Hz RB (DisplayPort) Video standards including HDTV 1080p - 60Hz and 4K-UHD (3840 x 2160) 60Hz Support for colour gamuts up to P3															
Inputs/Outputs	<table><tr><th colspan="3">Video & Computer</th></tr><tr><th>Type</th><th>Connector</th><th>Qty</th></tr><tr><td>HDMI 2.0b</td><td>HDMI</td><td>x 2</td></tr><tr><td>Display Port 1.2</td><td>DisplayPort</td><td>x 2</td></tr><tr><td>12G SDI IN</td><td>BNC</td><td>x 1</td></tr></table>	Video & Computer			Type	Connector	Qty	HDMI 2.0b	HDMI	x 2	Display Port 1.2	DisplayPort	x 2	12G SDI IN	BNC	x 1
Video & Computer																
Type	Connector	Qty														
HDMI 2.0b	HDMI	x 2														
Display Port 1.2	DisplayPort	x 2														
12G SDI IN	BNC	x 1														

	12G SDI OUT HDBaseT	BNC 8P8C "RJ45"	x 1 x 1																
	Communication & Control																		
	Type	Connector	Qty																
	3D Sync In	BNC	1																
	3D Sync Out (loop through)	BNC	1																
	3D Sync Out for IR	BNC	1																
	LAN / Art-Net	EtherCON RJ45	1																
	HDBaseT/Ethernet/RS232/IR	RJ45	1																
	Serial In RS-232C	9-pin D-Sub	1																
	Serial Out RS-232C	9-pin D-Sub	1																
	Wired Remote In	3.5mm Stereo Jack	1																
	Wired Remote Out	3.5mm Stereo Jack	1																
	12V Trigger 12V 350mA	3.5mm Stereo Jack	1																
	USB Power out 5V/2A	USB Type A	1																
3D Formats Supported	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential																		
HDTV Formats Supported	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), 4K-UHD (3840 x 2160), DCI 4K (4096 x 2160)																		
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, WQXGA																		
Bandwidth																			
Remote Control	Infrared/Wired Remote Control Unit																		
Automation Control	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control																		
Colour Temperature	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native)																		
Operation																			
illumination Type	Laser Phosphor. ECO mode support (80% Brightness)																		
Typical illumination Life	20,000 hours																		
Lenses	<table> <tr> <th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr> <tr> <td>0.31 - 0.33:1 zoom</td><td>124-318</td><td>0.38 - 3.01m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr> <tr> <td>0.55 - 0.75:1 zoom</td><td>124-319</td><td>0.69 - 6.58m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr> <tr> <td>0.74 - 1.08:1 zoom</td><td>124-320</td><td>0.75 - 12.19m</td><td>Vert: +/- 50%</td></tr> </table>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%	0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%	0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50%
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																
0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%																
0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%																
0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50%																

				Hor: +/- 20%
	1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%
	1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%
	2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%
	3.0 - 4.52:1 zoom	112-503	2.53 - 47.2m	Vert: +/- 45% Hor: +/- 10%
	4.46-6.94:1 zoom	112-504	3.71 - 76.7m	Vert: +/- 45% Hor: +/- 10%
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,			
Lens Mount	Centred lens for installation flexibility Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	990W (max)			
Thermal Dissipation	TBD			
Fan Noise	Normal mode: 40 dBA typical Eco Mode: Max 39 dBA			
Operating/Storage Temperature Operating:	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)			
Operating Humidity	90% (with maximum temperature of 35°C (95°F))			
Weight	29.4 kg / 64.8 lbs			
Dimensions	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch			
Safety & EMC Regulations	TBD			
Accessories	Accessory			Part No.
	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>			
Downloads	PDF CAD Drawings AUTOCAD Drawings			

**DIGITAL PROJECTION, INC****55 Chastain Road, Suite 115 Kennesaw, GA.****30144****T: 770.420.1350 | F: 770.420.1360****www.digitalprojection.com****DIGITAL PROJECTION, LTD****Greenside Way, Middleton Manchester, UK****M24 1XX****T: +44.161.947.3300 | F: +44.161.684.7674****www.digitalprojection.co.uk****DIGITAL PROJECTION, INC****55 Chastain Road, Suite 115 Kennesaw, GA.****30144****T: 770.420.1350 | F: 770.420.1360****www.digitalprojection.com****DIGITAL PROJECTION, CHINA****Rm A2301, Shaoyaoju 101 North Lane, Shi Ao****International Center, Chaoyang District, Beijing 100029,
PR China****T: +86.10.58239771 | F: +86 10 58239770**

Specifications subject to change without notice.
 ©2022 Digital Projection. DLP®, Digital Light
 Processing™ and DMD are trademarks of Texas
 Instruments, Inc



Certificate Number 13629
 ISO 9001