

[Click to Print This Page](#)



E-VISION 5000 UST

THE VISIONARIES CHOICE




E-Vision 5000 UST

5,000 ISO / 4,250 ISO Lumens | Contrast Ratio: 2,000,000:1 (FO/FO) | Part Number:

Key Specifications:

Colour System:	Laser Phosphor
DMD Specification:	Single chip 0.48" DMD
Aspect Ratio:	16x10
Fill Factor	
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 2.0• 2 x Digital Zoom• HSG Color Management• Sealed Engine• Auto Power On / Off <p>Geometry Correction & Lenses info</p> <ul style="list-style-type: none">• Keystone Adjustment 2D : V/H: +/- 15 steps (±15 Degree)• Image offset 122% (+/- 5%) <p>Colour Processing</p> <ul style="list-style-type: none">• 4 Segment (RGBY) / 2X Color Wheel• >90% Rec709

Source Compatibility	Graphics standards up to 1920 x 1200 resolution at 60Hz. Input support for 4K-UHD, 3840 x 2160										
Inputs/Outputs	Video & Computer										
	Type	Connector	Qty								
	VGA-In	VGA-In (15pin D-Sub)	1								
	HDMI 2.0	HDMI 2.0	2								
	.										
	Communication & Control										
	Type	Connector	Qty								
	Lan (RJ45)	RJ45	1								
	DC 12v Trigger (3.5mm Jack)	3.5mm Jack	1								
	RS-232 In	RS232	1								
3D Formats Supported	3D ready (DLP link, PC + Video), 3D Mandatory formats supported (Top/bottom, Side by Side, Frame Sequential).										
HDTV Formats Supported	720p, 1080i and 1080p										
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA										
Bandwidth											
Remote Control	IR remote control										
Automation Control	Alert Mail for Projector LAN Control-Crestron Roomview-Connected LAN Control-Crestron eControl LAN control - Extron LAN Control-PJ Link compatible LAN Control-AMX SSDP LAN to RS232 (RS232 by Telnet)										
Colour Temperature											
Operation											
illumination Type	Laser Light Source										
Typical illumination Life	15,000 hours										
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.25:1 (fixed)</td><td>N/A</td><td>0.336m - 0.739m</td><td>N/A</td></tr></table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.25:1 (fixed)	N/A	0.336m - 0.739m	N/A
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)								
0.25:1 (fixed)	N/A	0.336m - 0.739m	N/A								
Lens Mount	Manual focus										
Mechanical Mounting	Front/Rear Front/Rear Ceiling Two adjustable front feet Ceiling Mount compatible chassis with 4 off M4 mounting holes										
Orientation	Table Top or Inverted: Yes										

	Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	Normal Mode (100%): 370@240VAC Eco Mode (80%) 290W @240VAC			
Thermal Dissipation	Normal Mode (typical):1263 BTU/Hour @ 240VAC Eco Mode (Typical) 990 BTU/Hour at 240VAC			
Fan Noise	Normal Mode (Typical): 35 dBA / Eco 33 dBA			
Operating/Storage Temperature Operating:	Operating: 0° to 40°C (32°F to 104°F) Storage: -20° to 60°C (-4°F to -140°F)			
Operating Humidity	10% to 85% non-condensing			
Weight	9 kg / 19.8 lbs			
Dimensions	L: 405 mm W: 380 mm H: 150 mm (Excluding feet) L: 15.94 in W: 14.96 in H: 5.9 in			
Safety & EMC Regulations	FCC Class B, CE, CB, RoHS,			
Accessories	<table><tr><td>Accessory</td><td>Part No.</td></tr></table> <p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p>		Accessory	Part No.
Accessory	Part No.			
Downloads				
User Guide	User Guides Laser Risk Group Document Important Information (German) Important Information (French)			



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



Specifications subject to change without notice.

©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770



Certificate Number 13629
ISO 9001