

[Click to Print This Page](#)



E-VISION LASER 10K DIGITAL PROJECTOR

THE VISIONARIES CHOICE



E-Vision Laser 10K

10,000 ANSI / 11,250 ISO Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) 1,000:1 native | Part Number: 119-670

Key Specifications:

Colour System:	Laser Phosphor + 4-segment (RGBW) colour wheel for high brightness
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.• Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources• Dual Pipe Processing: Two sources in parallel for Left and Right eyes.• Synchronisation of active glasses.• 3GSDI with loop-through.• 24p and 1080p native display.• DICOM simulation mode. <p>Geometry Correction</p> <ul style="list-style-type: none">• Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.• Blanking control for custom input window sizing.• Scaling for fixed aspect ratio screens.

Edge Blending

- For independent edge and blend width adjustment.

Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

Projector Automation

- Real-time clock provides daily on/off automation.

Projector Maintenance Features


- Sealed optics.
- Long life 20,000 hour illumination.

Source Compatibility

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.
HDMI including Deep Color™ processing.
Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DisplayPort or VGA.
Component Video (SD and HD) via RGBHV.

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
DVI-D 1.0	DVI	1
DisplayPort 1.1a	DisplayPort	1
HDMI 1.4b	HDMI	2
3G-SDI in	BNC	1
3G-SDI out	BNC	1
VGA / Analog RGB	15-pin D-Sub	1
VGA Monitor out	15-pin D-Sub	1
Component Video	5 x BNC	1
HDBaseT (see LAN)	LAN RJ45	1
.		
Communication & Control		
Type	Connector	Qty
3D Sync Out	BNC	1
3D Sync In	BNC	1
LAN	RJ45	1
RS232	9-pin D-Sub	1
Wired Remote	3.5mm Stereo Jack	1
12V Trigger		

	<div>USB Power 5V/2A</div> <div>NOTE: The LAN port is shared with HDBase-T.</div> <div>NOTE: USB Power only for WHDI interfaces.</div>	<div>3.5mm Stereo Jack</div> <div>USB Type A</div>	<div>2</div> <div>1</div>																													
3D Formats Supported	<div>Frame Packing</div> <div>Dual Pipe</div> <div>Frame Sequential</div> <div>Side By Side (half)</div> <div>Top and Bottom</div>																															
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz, 60Hz), 720p (50, 60Hz)																															
Computer Compatibility	Up to 1920 x 1200																															
Bandwidth	<div>165 MHz on analog RGB</div> <div>165 Megapixels per second on HDMI</div>																															
Remote Control	<div>Addressable IR remote control, wireless and wired.</div> <div>On-Board keypad.</div>																															
Automation Control	<div>Crestron RoomView® Connected</div> <div>PJLink Class 1</div> <div>LAN</div> <div>RS-232</div> <div>AMX (Device Discovery)</div> <div>Served web page</div>																															
Colour Temperature	3200 to 9300K																															
Operation	<div></div>																															
illumination Type	Laser Light Source																															
Typical illumination Life	20,000 hours																															
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.38 :1 fixed</td><td>117-341</td><td>0.68m - 2.44m</td><td>Depends on image size, see Installation Guide.</td></tr><tr><td>0.75 - 0.93 :1 zoom</td><td>115-339</td><td>1.02m - 12.7m</td><td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td></tr><tr><td>0.76 :1 fixed</td><td>112-499</td><td>0.81m - 5.08m</td><td>none</td></tr><tr><td>1.25 - 1.79 :1 zoom</td><td>112-500</td><td>1.33m - 11.73m</td><td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td></tr><tr><td>1.73 - 2.27 :1 zoom</td><td>112-501</td><td>1.83m - 14.9m</td><td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td></tr><tr><td>2.22 - 3.67 :1 zoom</td><td>112-502</td><td>2.36m - 24.2m</td><td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2</td></tr></table>				Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.	0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	0.76 :1 fixed	112-499	0.81m - 5.08m	none	1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																													
0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.																													
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																													
0.76 :1 fixed	112-499	0.81m - 5.08m	none																													
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																													
1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																													
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2																													

				(R) frame
	3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
	5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,				
Lens Mount	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	Typical 1215W @ 240VAC in Normal mode Typical 960W @ 240VAC in ECO mode Typical 1270W @ 110VAC in Normal mode Typical 1000W @ 110VAC in ECO mode			
Thermal Dissipation	Typical 4146 BTU/Hour @ 240VAC in Normal mode Typical 3276 BTU/Hour @ 240VAC in ECO mode Typical 4334 BTU/Hour @ 110VAC in Normal mode Typical 3412 BTU/Hour @ 110VAC in ECO mode			
Fan Noise	Normal mode: 42 dBA Typical Eco mode: 39 dBA Typical			
Operating/Storage Temperature Operating:	Operating: 0 to 40C (32 to 104F) Operating: 40 to 45C (104 to 113F) w/ reduced light output Storage: -20 to 60C (-4 to 140F)			
Operating Humidity	10 to 90% relative, non-condensing			
Weight	28 kg / 62 lbs			
Dimensions	L: 59.83 cm x W: 50 cm x H: 21.85 cm L: 23.55 in x W: 19.68 in x H: 8.60 in			
Safety & EMC Regulations	CB, CE, FCC Class 1, KC, UL/cUL, CCC, RoHS 2 IEC EN 60825-1 Class 3R Laser Product, IEC EN 62471-5 Risk Group 2			
Accessories				
	Accessory		Part No.	
	Infrared Remote (replacement)		117-780	
*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.				
Downloads	PDF CAD Drawings			

	AUTOCAD Drawings STEP / IGS Drawings Lens CAD Drawings
User Guide	User Guides User Guides (German) User Guides (French) User Guides (Korean) Laser Risk Group Document Important Information Control Protocol Ultra Short Throw Lens Ultra Short Throw Lens Installation Guide



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



Specifications subject to change without notice.
 ©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
 ISO 9001



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

**International Center, Chaoyang District, Beijing 100029,
PR China**



T: +86.10.58239771 | F: +86 10 58239770