

[Click to Print This Page](#)



E-VISION LASER 13000 WU DIGITAL PROJECTOR

THE VISIONARIES CHOICE



E-Vision Laser 13000 WU

12,000 ANSI / 13,500 ISO Lumens | Contrast Ratio: 10,000:1 (Dynamic Black) 1,000:1 native | Part Number: 120-603

Key Specifications:

Colour System:	Blue and Red Lasers with Phosphor wheel and 3-segment colour wheel
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	<p>Red Laser Assist</p> <ul style="list-style-type: none">• Uses blue and red laser diodes for increased colour fidelity and highly accurate colours <p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 1.4b for Side by Side, Frame Packing, Frame Sequential & Top Bottom 3D formats.• Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources• Dual Pipe Processing: Two sources in parallel for Left and Right eyes.• Synchronisation of active glasses.• 3GSDI with loop-through.• 24p and 1080p native display.• DICOM simulation mode. <p>Geometry Correction</p>

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens.

Edge Blending

- For independent edge and blend width adjustment.

Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

Projector Automation

- Real-time clock provides daily on/off automation.

Projector Maintenance Features

- Sealed optics.
- Long life 20,000 hour illumination.

Source Compatibility


3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.
 HDMI including Deep Color™ processing.
 Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DisplayPort or VGA.
 Component Video (SD and HD) via RGBHV.

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DVI-D 1.0	DVI		3D Sync Out		
DisplayPort 1.1a	DisplayPort	1	3D Sync In	BNC	
HDMI 1.4b	HDMI	1	LAN	BNC	1
3G-SDI in	BNC	2	RS232	RJ45	1
3G-SDI out	BNC	1	Wired Remote	9-pin D-Sub	1
VGA / Analog RGB	15-pin D-Sub	1	12V Trigger	3.5mm	1
VGA Monitor out	15-pin D-Sub	1	NOTE: The LAN port is shared with HDBase-T.	Stereo Jack	1
Component Video	Sub	1		3.5mm	2
HDBaseT (see LAN)	5 x BNC LAN RJ45	1		Stereo Jack	

3D Formats Supported

Frame Packing

	Dual Pipe Frame Sequential Side By Side (half) Top and Bottom																																				
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)																																				
Computer Compatibility	Up to 1920 x 1200																																				
Bandwidth	165 MHz on analog RGB 165 Megapixels per second on HDMI																																				
Remote Control	Addressable IR remote control, wireless and wired. On-Board keypad.																																				
Automation Control	Crestron RoomView® Connected PJLink Class 1 LAN RS-232 AMX (Device Discovery) Served web page																																				
Colour Temperature	3200 to 9300K																																				
Operation																																					
illumination Type	Blue and Red Laser Light Source																																				
Typical illumination Life	20,000 hours																																				
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.38 :1 fixed</td> <td>117-341</td> <td>0.68m - 2.44m</td> <td>Depends on image size, see Installation Guide.</td> </tr> <tr> <td>0.75 - 0.93 :1 zoom</td> <td>115-339</td> <td>1.02m - 12.7m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td> </tr> <tr> <td>0.76 :1 fixed</td> <td>112-499</td> <td>0.81m - 5.08m</td> <td>none</td> </tr> <tr> <td>1.25 - 1.79 :1 zoom</td> <td>112-500</td> <td>1.33m - 11.73m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td> </tr> <tr> <td>1.73 - 2.27 :1 zoom</td> <td>112-501</td> <td>1.83m - 14.9m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td> </tr> <tr> <td>2.22 - 3.67 :1 zoom</td> <td>112-502</td> <td>2.36m - 24.2m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td> </tr> <tr> <td>3.58 - 5.38 :1 zoom</td> <td>112-503</td> <td>3.8m - 35.35m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td> </tr> <tr> <td>5.31 - 8.26 :1 zoom</td> <td>112-504</td> <td>5.59m - 54.8m</td> <td>Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame</td> </tr> </tbody> </table>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.	0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	0.76 :1 fixed	112-499	0.81m - 5.08m	none	1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame	5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																		
0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.																																		
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																																		
0.76 :1 fixed	112-499	0.81m - 5.08m	none																																		
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																																		
1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																																		
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																																		
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																																		
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame																																		
	* Lens focal ranges above are the optimised distances but are likely to focus further, please																																				

	contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,					
Lens Mount	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).					
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet					
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes					
Power Requirements	200-240VAC 50/60Hz single phase 7.8A 100-130VAC 50/60Hz single phase 11.5A Note: that in 100-130VAC operation, the projector will be at 70% brightness					
Power Consumption	Typical 1470W @ 240VAC in Normal mode Typical 1220W @ 240VAC in ECO mode Typical 1510W @ 240VAC in High Altitude mode Typical 1060W @ 110VAC in Normal mode Typical 1050W @ 110VAC in ECO mode Typical 1110W @ 110VAC in High Altitude mode					
Thermal Dissipation	Typical 5016 BTU/Hour @ 240VAC in Normal mode Typical 4163 BTU/Hour @ 240VAC in ECO mode Typical 5152 BTU/Hour @ 240VAC in High Altitude mode Typical 3617 BTU/Hour @ 110VAC in Normal mode Typical 3583 BTU/Hour @ 110VAC in ECO mode Typical 3787 BTU/Hour @ 110VAC in High Altitude mode					
Fan Noise	Normal mode: 48 dBA Max, 46 dBA Typical Eco mode: 44 dBA Max, 42 dBA Typical High Altitude Normal mode: 59 dBA Max, 57 dBA Typical High Altitude Eco Mode: 59 dBA Max, 57 dBA Typical					
Operating/Storage Temperature Operating:	Operating: 0 to 35C (32 to 95F) Operating: 35 to 40C (95 to 104F) w/ reduced light output Storage: -20 to 60C (-4 to 140F)					
Operating Humidity	10 to 90% relative, non-condensing					
Weight	31 kg / 68.3 lbs					
Dimensions	L: 59.83 cm x W: 50 cm x H: 21.85 cm L: 23.55 in x W: 19.68 in x H: 8.60 in					
Safety & EMC Regulations	UL / cUL, BIS, CB, CCC, KC, FCC (Part 15) Class A, FDA (Accession Number),CE, RoHS 2, IEC EN 60825-1-2014 Class 3R Laser Product, IEC EN 60825-1-2007 Class 1 Laser Product IEC EN 62471-5-2015 Risk Group 3					
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td>Infrared Remote (replacement)</td> <td>117-780</td> </tr> </tbody> </table> <p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p>		Accessory	Part No.	Infrared Remote (replacement)	117-780
Accessory	Part No.					
Infrared Remote (replacement)	117-780					
Downloads	PDF CAD Drawings					

	AUTOCAD Drawings STEP / IGS Drawings Lens CAD Drawings
User Guide	User Guides User Guides (German) User Guides (French) Laser Risk Group Document Important Information Important Information (German) Important Information (French) Control Protocol Ultra Short Throw Lens Ultra Short Throw Lens Installation Guide



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, LTD



Greenside Way, Middleton Manchester, UK

M24 1XX



T: +44.161.947.3300 | F: +44.161.684.7674



www.digitalprojection.co.uk



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



A Delta Group Company

Specifications subject to change without notice.
 ©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



Certificate Number 13629
 ISO 9001



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770