

[Click to Print This Page](#)



INSIGHT LASER 37000 8K

IMAGING BY: ASTRO

THE VISIONARIES CHOICE




INSIGHT LASER 37000 8K (Preliminary)

37,000 ISO Lumens | Contrast Ratio: 2,000:1 Native | Part Number: 120-782

Key Specifications:

Colour System:	Laser Phosphor with ColorBoost + Red Laser		
Display Type:	3 x 1.38" DarkChip 3 DMD , +/- 12° tilt angle		
DMD Specification:	Displays 8K-UHD 7680x4320, 4096 x 2160 native		
Aspect Ratio:	1.9:1		
Fill Factor	87%		
Key Features:	<p>Colour Processing</p> <ul style="list-style-type: none">• Powerful seven point colour correction for accurate colour matching.• Selectable de-gamma curves• Individual R,G,B lifts and gains <p>Projector Controller Software</p> <ul style="list-style-type: none">• Intuitive user interface for network control.• Simultaneous control of user-defined groups of projectors.• At-a-glance monitoring of projector status.		
Source Compatibility	Up to 7680x4320 resolution at 60Hz via DisplayPort, SDI or HDMI. Up to 7680x4320 resolution at 120Hz via 12G SDI		
Inputs/Outputs	Video & Computer		
	Type	Connector	Qty

	<table border="1"> <tr> <td>3G-SDI</td> <td>BNC</td> <td>16</td> </tr> <tr> <td>12G-SDI</td> <td>BNC</td> <td>8</td> </tr> <tr> <td>HDMI</td> <td>HDMI</td> <td>4</td> </tr> <tr> <td>DisplayPort</td> <td>DisplayPort</td> <td>2</td> </tr> </table>	3G-SDI	BNC	16	12G-SDI	BNC	8	HDMI	HDMI	4	DisplayPort	DisplayPort	2																				
3G-SDI	BNC	16																															
12G-SDI	BNC	8																															
HDMI	HDMI	4																															
DisplayPort	DisplayPort	2																															
	<table border="1"> <tr> <th colspan="3">Communication & Control</th> </tr> <tr> <th>Type</th> <th>Connector</th> <th>Qty</th> </tr> <tr> <td>LAN</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td>RS-232</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Wired Remote</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>Sync</td> <td>BNC (TBC)</td> <td>1</td> </tr> </table>	Communication & Control			Type	Connector	Qty	LAN	RJ45	1	RS-232	9-pin D-Sub	1	Wired Remote	3.5mm Stereo Jack	1	Sync	BNC (TBC)	1														
Communication & Control																																	
Type	Connector	Qty																															
LAN	RJ45	1																															
RS-232	9-pin D-Sub	1																															
Wired Remote	3.5mm Stereo Jack	1																															
Sync	BNC (TBC)	1																															
3D Formats Supported	Dual Pipe 7680 x 4320 @ 120Hz (TBC) via 12G SDI																																
HDTV Formats Supported	4096 x 2160p (24, 59.94, 60 Hz) 3840 x 2160p (24, 59.94, 60 Hz) 1080p (24, 59, 94, 60 Hz)																																
Computer Compatibility	Up to 7680x4320																																
Bandwidth	N/A																																
Remote Control	Addressable IR remote Control, Wireless and wired. On-Board keypad.																																
Automation Control	RS232 LAN																																
Colour Temperature	3200K to 9300K																																
Operation																																	
illumination Type	Laser Light Source																																
Typical illumination Life	20,000 hours																																
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>7680 X 4320</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.21 - 1.83:1 zoom</td> <td>115-627</td> <td>2.5m - 100m</td> <td>Vert: 0.40 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.14 (R) frame</td> </tr> <tr> <td>1.76 - 2.77:1 zoom</td> <td>115-630</td> <td>3.5m - 100m</td> <td>Vert: 0.45 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.17 (R) frame</td> </tr> <tr> <td>2.70 - 5.31:1 zoom</td> <td>115-632</td> <td>4.5m - 100m</td> <td>Vert: 0.42 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.17 (R) frame</td> </tr> <tr> <td>At Native 4K</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.13 - 1.72:1</td> <td>115-627</td> <td>2.5m - 100m</td> <td>Vert: 0.34 (U) 0.19 (D) frame, Hor: 0.08 (L) 0.10 (R) frame</td> </tr> <tr> <td>1.65 - 2.60:1</td> <td>115-630</td> <td>3.5m - 100m</td> <td>Vert: 0.40 (U) 0.20 (D) frame, Hor: 0.13</td> </tr> </tbody> </table>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	7680 X 4320	-	-	-	1.21 - 1.83:1 zoom	115-627	2.5m - 100m	Vert: 0.40 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.14 (R) frame	1.76 - 2.77:1 zoom	115-630	3.5m - 100m	Vert: 0.45 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.17 (R) frame	2.70 - 5.31:1 zoom	115-632	4.5m - 100m	Vert: 0.42 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.17 (R) frame	At Native 4K	-	-	-	1.13 - 1.72:1	115-627	2.5m - 100m	Vert: 0.34 (U) 0.19 (D) frame, Hor: 0.08 (L) 0.10 (R) frame	1.65 - 2.60:1	115-630	3.5m - 100m	Vert: 0.40 (U) 0.20 (D) frame, Hor: 0.13
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																														
7680 X 4320	-	-	-																														
1.21 - 1.83:1 zoom	115-627	2.5m - 100m	Vert: 0.40 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.14 (R) frame																														
1.76 - 2.77:1 zoom	115-630	3.5m - 100m	Vert: 0.45 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.17 (R) frame																														
2.70 - 5.31:1 zoom	115-632	4.5m - 100m	Vert: 0.42 (U) 0.20 (D) frame, Hor: 0.10 (L) 0.17 (R) frame																														
At Native 4K	-	-	-																														
1.13 - 1.72:1	115-627	2.5m - 100m	Vert: 0.34 (U) 0.19 (D) frame, Hor: 0.08 (L) 0.10 (R) frame																														
1.65 - 2.60:1	115-630	3.5m - 100m	Vert: 0.40 (U) 0.20 (D) frame, Hor: 0.13																														

			(L) 0.13 (R) frame				
	2.53 - 4.98:1	115-632	4.5m - 100m				
			Vert: 0.37 (U) 0.20 (D) frame, Hor: 0.13 (L) 0.13 (R) frame				
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,						
Lens Mount	Motorised shift, zoom and focus. Intelligent Lens Memory with user-definable preset positions.						
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear feet Built-in stacking points Eye-bolts for handling a single projector Optional mounting/grab rail						
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes						
Power Requirements	200-240VAC 50/60Hz single phase Power connector: 32A Ceeform (Europe) or L6 30P (USA)						
Power Consumption	3800W @ 240VAC						
Thermal Dissipation	12965 BTU/Hour @ 240VAC (TBC)						
Fan Noise	52dBA						
Operating/Storage Temperature:	Operating: 0 to 35C (32 to 95F) Storage: -20 to 60C (-4 to 140F)						
Operating Humidity	10 to 90% non-condensing						
Weight	132 kg / 291 lbs						
Dimensions	L: 113.0cm W: 75.0cm H: 49.3cm L: 44.5 inch W: 29.5 inch H: 19.4 inch						
Safety & EMC Regulations	UL / cUL, CB, CE, FCC Class A, IEC EN 60825-1 Class 3R Laser Product, IEC EN 62471-5 Risk Group 3, BSMI, FDA, CCC						
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td>Replacement filter set</td> <td>120-784</td> </tr> </tbody> </table> <p><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></p>			Accessory	Part No.	Replacement filter set	120-784
Accessory	Part No.						
Replacement filter set	120-784						
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings						
User Guide							



DIGITAL PROJECTION, LTD



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



www.digitalprojection.com



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770



Specifications subject to change without notice.
©2024 Digital Projection. DLP®, Digital Light
Processing™ and DMD are trademarks of Texas
Instruments, Inc

A brand of 