



E-Vision 7520 WU

7,700 ISO / 6,900 ANSI Lumens | Contrast Ratio: 3,000,000:1 (Dynamic Black) | Part Number: 124-449

Key Specifications:

Colour System:	Laser Phosphor with colourwheel
Display Type:	1 x 0.65" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native resolution. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDR processing• Two projectors in one - 4K-UHD and WQXGA+.• DisplayPort 1.2.• 2 x HDMI 2.0.• 2 x HDMI 1.4b for Dual Pipe processing and Frame Sequential 3D format.• Sequential Processing: 3D via single HDMI 1.4b input.• Dual Pipe Processing: 3D Left and Right Eyes via two HDMI 1.4b inputs.• Synchronisation of active glasses.• 3G-SDI with loop-through.• DICOM simulation mode. <p>Geometry Correction</p> <ul style="list-style-type: none">• Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc and Image Rotation.• Non-linear warp.• Digital zoom, pan and scan.• Blanking control for custom input window sizing.• Scaling available for fixed aspect ratio screens.• Unscaled processing for pixel mapped display. <p>Edge Blending</p>

- Blending control available for all sides with width control.
- Correction for non-active pixels at the edge of the display.

Picture in Picture

- Two sources can be displayed simultaneously using 2D inputs: either picture in picture (PIP), or side by side (PBP), with original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 100m from source with low cost cabling.
- Supports up to 4K UHD 3840 x 2160@60Hz 4:2:0 or 4K UHD 3840 x 2160@30Hz 4:4:4

Colour Processing

- Four colour modes available.
- Powerful seven point colour correction for accurate colour matching with presets.
- Easy colour temperature selection.
- Manual seven point colour adjustment.
- Traditional lifts and gains.

Projector Controller Software

- Intuitive user interface for network control.
- Simultaneous control of user-defined groups of projectors.
- At-a-glance monitoring of projector status.

Projector Automation

- Real-time clock provides daily on/off automation.
- E-mail alerts for system status.

Source Compatibility

2D graphics standards up to 4K-UHD 3840 x 2160 resolution at 60Hz via HDMI 2.0, HDBaseT (4:2:0) and DisplayPort inputs.

3D graphics standards up to WQXGA at 120Hz DualPipe via HDMI 1.4b inputs.

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

WQXGA+ mode

2D sources up to WQXGA+ at 120Hz can be displayed scaled to fit WQXGA+.

3D sources up to WQXGA at 120Hz can be displayed scaled to fit WQXGA+.

4K-UHD mode

2D sources up to 4K-UHD will be displayed scaled to fit 4K-UHD.


Auto mode

Sources greater than WQXGA+ will be displayed scaled to fit 4K-UHD.

Sources up to WQXGA+ will be displayed scaled to fit WQXGA+.

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
DisplayPort 1.2 (2D)	DisplayPort	1
HDMI 1.4b (3D)	HDMI	2
HDMI 2.0 (2D)	HDMI	2
3G-SDI in (2D)	BNC	1
3G-SDI out	BNC	1
HDBaseT (see LAN) (2D)	RJ45	1
Communication & Control		
Type	Connector	Qty

	3D Sync Out 3D Sync In LAN RS232 Wired Remote 12V Trigger 3D Sync IR Out NOTE: One of the LAN ports is shared with HDBase-T.	BNC BNC RJ45 9-pin D Sub 3.5mm Stereo Jack 3.5mm Stereo Jack BNC	1 1 2 1 1 2 1									
3D Formats Supported	Frame Sequential Dual-Pipe											
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz, 100Hz, 120Hz) 1080i (50Hz, 60Hz) 720p (50, 60Hz) 2K (24Hz, 25Hz, 30Hz, 50Hz, 60Hz) 4K-UHD (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)											
Computer Compatibility	2D 4K-UHD up to 60Hz. WQXGA+ up to 120Hz. 3D Supported formats will be displayed within WQXGA+.											
Bandwidth	498 megapixels per second via DisplayPort and HDMI 2.0.											
Remote Control	Addressable IR remote control, wireless and wired. On-Board keypad											
Automation Control	Crestron RoomView® Connected PJLink Class 1 LAN RS232 AMX (Device Discovery) Served web pages (projector status, projector control, Crestron RoomView®, network settings, alert mail setup, time setup, error log, On Screen Display)											
Colour Temperature	3200K to 9300K											
Operation												
illumination Type	Laser Light Source											
Typical illumination Life	30,000 hours											
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>1.15 - 1.9:1 (fixed)</td> <td>N/A</td> <td>1.5m - 5m (Optical range) 1.5m - 8m (Mechanical range)</td> <td>Vert: Fixed Offset 0.65 (U) frame with small variable vertical and horizontal shift</td> </tr> </tbody> </table>				Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	1.15 - 1.9:1 (fixed)	N/A	1.5m - 5m (Optical range) 1.5m - 8m (Mechanical range)	Vert: Fixed Offset 0.65 (U) frame with small variable vertical and horizontal shift
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)									
1.15 - 1.9:1 (fixed)	N/A	1.5m - 5m (Optical range) 1.5m - 8m (Mechanical range)	Vert: Fixed Offset 0.65 (U) frame with small variable vertical and horizontal shift									
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,											

Lens Mount	Manual focus and zoom				
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet				
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes				
Power Requirements	100-130VAC and 200-240VAC selectable, 50/60Hz single phase				
Power Consumption	950 W @220 Vac (1000 W @110 Vac)				
Thermal Dissipation	Max 3139 BTU/hour @100 VAC Max 3002 BTU/hour @240 VAC				
Fan Noise	Smooth Picture On: <i>Normal mode:</i> typical 40 (max 42) dBA <i>Eco2 mode:</i> typical 37 (max 39) dBA Smooth Picture Off: <i>Normal mode:</i> typical 38 (max 40) dBA <i>Eco2 mode:</i> typical 34 (max 36) dBA				
Operating/Storage Temperature:	Operating: 5 to 40C (41 to 104F) Storage: -10 to 60C (14 to 140F)				
Operating Humidity	10 to 85% non-condensing				
Weight	13 kg / 28.7 lbs				
Dimensions	L: 59.83 cm x W: 50 cm x H: 21.85 cm L: 23.55 in x W: 19.68 in x H: 8.60 in				
Safety & EMC Regulations	CE, FCC Class A, CCC, UL/cUL, FDA CB, KC, CEL, CECP				
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td colspan="2">*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</td> </tr> </tbody> </table>	Accessory	Part No.	*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.	
Accessory	Part No.				
*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.					
Downloads					
User Guide					



DIGITAL PROJECTION, LTD



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



www.digitalprojection.com



DIGITAL PROJECTION, INC

DIGITAL  **PROJECTION**

Specifications subject to change without notice.
©2024 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770

A brand of  DELTA