

[Click to Print This Page](#)



E-Vision 6320 WU

6,500 ISO / 5,700 ANSI Lumens | Contrast Ratio: 3,000,000:1 (Dynamic Black) | Part Number: TBD

Key Specifications:

Colour System:	Laser Phosphor with colourwheel
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native resolution. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDR processing• Two projectors in one - 4K-UHD and WQXGA+.• DisplayPort 1.2.• 2 x HDMI 2.0.• 2 x HDMI 1.4b for Dual Pipe processing and Frame Sequential 3D format.• Sequential Processing: 3D via single HDMI 1.4b input.• Dual Pipe Processing: 3D Left and Right Eyes via two HDMI 1.4b inputs.• Synchronisation of active glasses.• 3G-SDI with loop-through.• DICOM simulation mode. <p>Geometry Correction</p> <ul style="list-style-type: none">• Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc and Image Rotation.• Non-linear warp.• Digital zoom, pan and scan.• Blanking control for custom input window sizing.• Scaling available for fixed aspect ratio screens.• Unscaled processing for pixel mapped display. <p>Edge Blending</p> <ul style="list-style-type: none">• Blending control available for all sides with width control.• Correction for non-active pixels at the edge of the display.

Picture in Picture

- Two sources can be displayed simultaneously using 2D inputs: either picture in picture (PIP), or side by side (PBP), with original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 100m from source with low cost cabling.
- Supports up to 4K UHD 3840 x 2160@60Hz 4:2:0 or 4K UHD 3840 x 2160@30Hz 4:4:4

Colour Processing

- Four colour modes available.
- Powerful seven point colour correction for accurate colour matching with presets.
- Easy colour temperature selection.
- Manual seven point colour adjustment.
- Traditional lifts and gains.

Projector Controller Software

- Intuitive user interface for network control.
- Simultaneous control of user-defined groups of projectors.
- At-a-glance monitoring of projector status.

Projector Automation

- Real-time clock provides daily on/off automation.
- E-mail alerts for system status.

Source Compatibility

2D graphics standards up to 4K-UHD 3840 x 2160 resolution at 60Hz via HDMI 2.0, HDBaseT (4:2:0) and DisplayPort inputs.

3D graphics standards up to WQXGA at 120Hz DualPipe via HDMI 1.4b inputs.

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

WQXGA+ mode

2D sources up to WQXGA+ at 120Hz can be displayed scaled to fit WQXGA+.

3D sources up to WQXGA at 120Hz can be displayed scaled to fit WQXGA+.

4K-UHD mode

2D sources up to 4K-UHD will be displayed scaled to fit 4K-UHD.


Auto mode

Sources greater than WQXGA+ will be displayed scaled to fit 4K-UHD.


Sources up to WQXGA+ will be displayed scaled to fit WQXGA+.


Inputs/Outputs

Video & Computer		
Type	Connector	Qty
DisplayPort 1.2 (2D)	DisplayPort	1
HDMI 1.4b (3D)	HDMI	2
HDMI 2.0 (2D)	HDMI	2
3G-SDI in (2D)	BNC	1
3G-SDI out	BNC	1
HDBaseT (see LAN) (2D)	RJ45	1
Communication & Control		
Type	Connector	Qty
3D Sync Out	BNC	1
3D Sync In	BNC	1
LAN	RJ45	2

	<div>RS232</div> <div>Wired Remote</div> <div>12V Trigger</div> <div>3D Sync IR Out</div> <div>NOTE: One of the LAN ports is shared with HDBase-T.</div>	<div>9-pin D Sub</div> <div>3.5mm Stereo Jack</div> <div>3.5mm Stereo Jack</div> <div>BNC</div>	<div>1</div> <div>1</div> <div>2</div> <div>1</div>								
3D Formats Supported	Frame Sequential Dual-Pipe										
HDTV Formats Supported	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz, 100Hz, 120Hz) 1080i (50Hz, 60Hz) 720p (50, 60Hz) 2K (24Hz, 25Hz, 30Hz, 50Hz, 60Hz) 4K-UHD (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)										
Computer Compatibility	2D 4K-UHD up to 60Hz. WQXGA+ up to 120Hz. 3D Supported formats will be displayed within WQXGA+.										
Bandwidth	498 megapixels per second via DisplayPort and HDMI 2.0.										
Remote Control	Addressable IR remote control, wireless and wired. On-Board keypad										
Automation Control	Crestron RoomView® Connected PJLink Class 1 LAN RS232 AMX (Device Discovery) Served web pages (projector status, projector control, Crestron RoomView®, network settings, alert mail setup, time setup, error log, On Screen Display)										
Colour Temperature	3200K to 9300K										
Operation											
illumination Type	Laser Light Source										
Typical illumination Life	30,000 hours										
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>2.49 - 3.18, f = 17.23 - 27.97mm</td><td>TBD</td><td>1.5m - 8m (TBD)</td><td>V: Above +95%~+109%, H: Above +/-2%</td></tr></table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	2.49 - 3.18, f = 17.23 - 27.97mm	TBD	1.5m - 8m (TBD)	V: Above +95%~+109%, H: Above +/-2%
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)								
2.49 - 3.18, f = 17.23 - 27.97mm	TBD	1.5m - 8m (TBD)	V: Above +95%~+109%, H: Above +/-2%								
Lens Mount	Manual focus and zoom										
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet										


Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes	
Power Requirements	100-130VAC and 200-240VAC selectable, 50/60Hz single phase	
Power Consumption	950 W @220 Vac (1000 W @110 Vac)	
Thermal Dissipation	Max 3139 BTU/hour @100 VAC Max 3002 BTU/hour @240 VAC	
Fan Noise	35 dB / 31dB (TBD)	
Operating/Storage Temperature:	Operating: 5 to 40C (41 to 104F) Storage: -10 to 60C (14 to 140F)	
Operating Humidity	10 to 85% non-condensing	
Weight	28.15 kg / 62 lbs	
Dimensions	L: 38.0 cm x W: 49.6 cm x H: 16.0 cm L: 14.9 in x W: 19.5 in x H: 6.2 in	
Safety & EMC Regulations	CE, FCC Class A, CCC, UL/cUL, FDA CB, KC, CEL, CECP	
Accessories		
	Accessory	Part No.
*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.		
Downloads		
User Guide		


 **DIGITAL PROJECTION, LTD**


 Unit 3, Aniseed Park, Broadgate,
Oldham, UK OL9 9XA


 T: +44 (0)161 947 3300

 www.digitalprojection.com

 **DIGITAL PROJECTION, INC**

 55 Chastain Road, Suite 115 Kennesaw, GA.
30144

 T: 770.420.1350 | F: 770.420.1360

 www.digitalprojection.com



Specifications subject to change without notice.
©2024 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc





DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

**International Center, Chaoyang District, Beijing 100029,
PR China**



T: +86.10.58239771 | F: +86 10 58239770