

[Click to Print This Page](#)



## E-Vision 16000i DIGITAL PROJECTOR

THE VISIONARIES CHOICE



## E-Vision 16000i WU (Preliminary)

**16,000 ISO / 14,500 ANSI Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part Number: 123-522**

### Key Specifications:

<b>Colour System:</b>	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 4 Segment RGBY 2 x 7200rpm (120Hz)
<b>Display Type:</b>	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
<b>DMD Specification:</b>	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
<b>Aspect Ratio:</b>	16x10
<b>Fill Factor</b>	
<b>Key Features:</b>	<b>Video &amp; Graphics Processing</b> <ul style="list-style-type: none"><li>• Nexus electronics platform</li><li>• HDMI 2.0</li><li>• DisplayPort 1.2</li><li>• 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours</li><li>• Hue, Saturation and Gain colour management.</li><li>• 24p and 1080p native display.</li><li>• HDR support</li><li>• Input source automatically detected</li><li>• Selectable Dynamic Black</li><li>• Synchronisation of active glasses or polarising switcher.</li></ul>

- DICOM simulation mode
- Optics engine sealed to IP6X

#### Geometry Correction

- Vertical & Horizontal Keystone correction
- Four Corner adjustment
- Rotation -100 to +100 with +/- 0.25° per step
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled
- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

#### Edge Blending

- Correction for non-active pixels at the edge of the display.

#### HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

#### Colour Processing

- Powerful seven point colour correction for accurate colour matching.

#### Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

#### Source Compatibility

3G-SDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.


Graphics standards up to WQXGA 2560 x 1600 60 Hz RB (DisplayPort)

Video standards up to HDTV 1080p - 60Hz, with support for 4K-UHD (3840 x 2160) 60Hz

Display Support for 3840 x 2160 (4K-UHD) up to 60Hz and 4096 x 2160 (4K) up to 60Hz

#### Inputs/Outputs

Video & Computer		
Type	Connector	Qty
HDMI 2.0 (HDCP compatible)	HDMI	2
DisplayPort 1.2	DisplayPort	2
HDBaseT	8P8C "RJ45"	1
3G-SDI in	BNC	1
3G-SDI out	BNC	1
Communication & Control		

	<table><tr><th>Type</th><th>Connector</th><th>Qty</th></tr><tr><td>3D Sync In</td><td>BNC</td><td>1</td></tr><tr><td>3D Sync Out (loop through)</td><td>BNC</td><td>1</td></tr><tr><td>3D Sync Out for IR</td><td>BNC</td><td>1</td></tr><tr><td>LAN / Art-Net</td><td>EtherCON RJ45</td><td>1</td></tr><tr><td>HDBaseT/Ethernet/RS232/IR</td><td>RJ45</td><td>1</td></tr><tr><td>Serial In RS-232C</td><td>9-pin D-Sub</td><td>1</td></tr><tr><td>Serial Out RS-232C</td><td>9-pin D-Sub</td><td>1</td></tr><tr><td>Wired Remote In</td><td>3.5mm Stereo Jack</td><td>1</td></tr><tr><td>Wired Remote Out</td><td>3.5mm Stereo Jack</td><td>1</td></tr><tr><td>12V Trigger 12V 350mA</td><td>3.5mm Stereo Jack</td><td>1</td></tr><tr><td>USB Power out 5V/2A</td><td>USB Type A</td><td>1</td></tr></table>	Type	Connector	Qty	3D Sync In	BNC	1	3D Sync Out (loop through)	BNC	1	3D Sync Out for IR	BNC	1	LAN / Art-Net	EtherCON RJ45	1	HDBaseT/Ethernet/RS232/IR	RJ45	1	Serial In RS-232C	9-pin D-Sub	1	Serial Out RS-232C	9-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1	Wired Remote Out	3.5mm Stereo Jack	1	12V Trigger 12V 350mA	3.5mm Stereo Jack	1	USB Power out 5V/2A	USB Type A	1
Type	Connector	Qty																																			
3D Sync In	BNC	1																																			
3D Sync Out (loop through)	BNC	1																																			
3D Sync Out for IR	BNC	1																																			
LAN / Art-Net	EtherCON RJ45	1																																			
HDBaseT/Ethernet/RS232/IR	RJ45	1																																			
Serial In RS-232C	9-pin D-Sub	1																																			
Serial Out RS-232C	9-pin D-Sub	1																																			
Wired Remote In	3.5mm Stereo Jack	1																																			
Wired Remote Out	3.5mm Stereo Jack	1																																			
12V Trigger 12V 350mA	3.5mm Stereo Jack	1																																			
USB Power out 5V/2A	USB Type A	1																																			
3D Formats Supported	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential																																				
HDTV Formats Supported	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N), SECAM (B,D,G,K,K1,L) Display Support for 2K 2048 x 1080 up to 60Hz and 4K-UHD 3840 x 2160 up to 60Hz																																				
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA up to 120hz RB, Mac																																				
Bandwidth																																					
Remote Control	Infrared Remote Control Unit																																				
Automation Control	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control																																				
Colour Temperature	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native )																																				
Operation																																					
illumination Type	Laser Phosphor. ECO mode support (80% Brightness)																																				
Typical illumination Life	20,000 hours																																				
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.31 - 0.33:1 zoom</td><td>124-318</td><td>0.38 - 3.01m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr><tr><td>0.55 - 0.75:1 zoom</td><td>124-319</td><td>0.69 - 6.58m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr><tr><td>0.74 - 1.08:1 zoom</td><td>124-320</td><td>0.75 - 12.19m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr><tr><td>1.05 - 1.41:1 zoom</td><td>124-321</td><td>1.06 - 18.94m</td><td>Vert: +/- 60% Hor: +/- 20%</td></tr></table>				Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%	0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%	0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%	1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%													
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																		
0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%																																		
0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%																																		
0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%																																		
1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%																																		

	1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%
	2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%
	3.0 - 4.52:1 zoom	112-503	2.53 - 47.2m	Vert: +/- 45% Hor: +/- 10%
	4.46-6.94:1 zoom	112-504	3.71 - 76.7m	Vert: +/- 45% Hor: +/- 10%
* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,				
<b>Lens Mount</b>	Centred lens for installation flexibility Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
<b>Mechanical Mounting</b>	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm			
<b>Orientation</b>	<b>Table Top or Inverted:</b> Yes <b>Pointing Up:</b> Yes <b>Pointing Down:</b> Yes <b>Roll (Portrait):</b> Yes			
<b>Power Requirements</b>	100-240VAC 50/60Hz single phase 6.8A			
<b>Power Consumption</b>	900W (Max)			
<b>Thermal Dissipation</b>	At 100VAC - Typical 3276 BTU/hr, Max 3604 BTU/hr in Normal mode At 100VAC - Typical 2595 BTU/hr, Max 2853 BTU/hr in Eco mode At 100VAC - Typical 2662 BTU/hr, Max 2928 BTU/hr in High Altitude Mode At 220VAC - Typical 3174 BTU/hr, Max 3492 BTU/hr in Normal mode At 220VAC - Typical 2491 BTU/hr, Max 2740 BTU/hr in Eco mode At 220VAC - Typical 2560 BTU/hr, Max 2816 BTU/hr in High Altitude Mode			
<b>Fan Noise</b>	Normal mode: 39 dBA typical, Max 41 dBA Eco Mode: 36 dBA typique / Max 38 dBA			
<b>Operating/Storage Temperature:</b>	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)			
<b>Operating Humidity</b>	90% (with maximum temperature of 35°C (95°F))			
<b>Weight</b>	29.4 kg / 64.8 lbs			
<b>Dimensions</b>	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch			
<b>Safety &amp; EMC Regulations</b>	cTUVus, CB report, CCC (China), CECP (China Energy Conservation Program), China RoHS, FCC part 15 Class A, FDA 21 CFR part 1040 (Except with respect to those characteristics authorised by Variance Number 2021-V-0192, CE (European Economic Area), UKCA (United Kingdom), KC (Korea), BSMI (Taiwan), RCM (Australia), IEC 60825-1 : 2014 - Class 1 Laser Product, IEC EN 62471-5:2015 - Risk Group 2 This projector may become Risk Group 3 when an interchangeable lens with a throw ratio of greater than 1.94:1 is installed Such combinations of projector and lens are intended for professional use only and are not intended for consumer use.			

Accessories	Accessory	Part No.
	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>	
Downloads	<a href="#">PDF CAD Drawings</a> <a href="#">AUTOCAD Drawings</a> <a href="#">STEP / IGS Drawings</a>	
User Guide	<a href="#">User Guides</a> <a href="#">Laser Risk Group Document</a> <a href="#">Important Information (German)</a> <a href="#">Important Information (French)</a> <a href="#">Control Protocol</a>	




**DIGITAL PROJECTION, LTD**  
 Unit 3, Aniseed Park, Broadgate,  
Oldham, UK OL9 9XA  
 T: +44 (0)161 947 3300  
 [www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, INC**  
 55 Chastain Road, Suite 115 Kennesaw, GA.  
30144  
 T: 770.420.1350 | F: 770.420.1360  
 [www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, CHINA**  
 Rm A2301, Shaoyaoju 101 North Lane, Shi Ao  
International Center, Chaoyang District, Beijing 100029,  
PR China  
 T: +86.10.58239771 | F: +86 10 58239770



Specifications subject to change without notice.  
©2024 Digital Projection. DLP®, Digital Light  
Processing™ and DMD are trademarks of Texas  
Instruments, Inc

A brand of 