

[Click to Print This Page](#)



E-VISION 15000i 4K+

THE VISIONARIES CHOICE



E-Vision 15000i 4K+ (Preliminary)

15,000 ISO / 13,500 ANSI Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part Number: 124-361

Key Specifications:

Colour System:	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 8 Segment RGBYRGBY 2 x 7200rpm (120Hz)
Display Type:	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
DMD Specification:	1920 x 1200 pixels native display. (3840 x 2400 via 4-way pixel shift technology) Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	Video & Graphics Processing • Nexus electronics platform • HDMI 2.0 • DisplayPort 1.2 • 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours • Hue, Saturation and Gain colour management. • 24p and 1080p native display. • HDR support • Input source automatically detected • Selectable Dynamic Black • DICOM simulation mode

- Optics engine sealed to IP6X

Geometry Correction

- Vertical & Horizontal Keystone correction
- Four Corner adjustment
- Rotation -100 to +100 with +/- 0.25° per step
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled
- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

Edge Blending

- Correction for non-active pixels at the edge of the display.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

Source Compatibility

12G-SDI, Supports a high data transfer rate of up to 12 gigabits per second (Gbps), enabling the transmission of uncompressed 4K UHD (Ultra High Definition) video signals with a single connector

Graphics standards up to WUXGA 1920 x 1200 - 120Hz RB, Up to WQXGA 2560 x 1600 60Hz RB (DisplayPort)

Video standards including HDTV 1080p - 60Hz and 4K-UHD (3840 x 2160) 60Hz

Support for colour gamuts up to P3

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
HDMI 2.0b	HDMI	x 2
Display Port 1.2	DisplayPort	x 2
12G SDI IN	BNC	x 1
12G SDI OUT	BNC	x 1
HDBaseT	8P8C "RJ45"	x 1

	Communication & Control		
	Type	Connector	Qty
	3D Sync In	BNC	1
	3D Sync Out (loop through)	BNC	1
	3D Sync Out for IR	BNC	1
	LAN / Art-Net	EtherCON RJ45	1
	HDBaseT/Ethernet/RS232/IR	RJ45	1
	Serial In RS-232C	9-pin D-Sub	1
	Serial Out RS-232C	9-pin D-Sub	1
	Wired Remote In	3.5mm Stereo Jack	1
	Wired Remote Out	3.5mm Stereo Jack	1
	12V Trigger 12V 350mA	3.5mm Stereo Jack	1
	USB Power out 5V/2A	USB Type A	1
3D Formats Supported	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential		
HDTV Formats Supported	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), 4K-UHD (3840 x 2160), DCI 4K (4096 x 2160)		
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, WQXGA		
Bandwidth			
Remote Control	Infrared/Wired Remote Control Unit		
Automation Control	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control		
Colour Temperature	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native)		
Operation			
illumination Type	Laser Phosphor. ECO mode support (80% Brightness)		
Typical illumination Life	20,000 hours		
Lenses	Lens	Part No.	Optimised Focus Range*
	0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m
	0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m
	0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m
	1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m
			Vert: +/- 50% Hor: +/- 20%
			Vert: +/- 50% Hor: +/- 20%
			Vert: +/- 50% Hor: +/- 20%
			Vert: +/- 60%

				Hor: +/- 20%
	1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%
	2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%
	3.0 - 4.52:1 zoom	112-503	2.53 - 47.2m	Vert: +/- 45% Hor: +/- 10%
	4.46-6.94:1 zoom	112-504	3.71 - 76.7m	Vert: +/- 45% Hor: +/- 10%
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,			
Lens Mount	Centred lens for installation flexibility Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	990W (max)			
Thermal Dissipation	TBD			
Fan Noise	Normal mode: 40 dBA typical Eco Mode: Max 39 dBA			
Operating/Storage Temperature:	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)			
Operating Humidity	90% (with maximum temperature of 35°C (95°F))			
Weight	29.4 kg / 64.8 lbs			
Dimensions	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch			
Safety & EMC Regulations	TBD			
Accessories				
	Accessory		Part No.	
	*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.			
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings			



DIGITAL PROJECTION, LTD



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



www.digitalprojection.com



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770

DIGITAL **PROJECTION**

Specifications subject to change without notice.
©2024 Digital Projection. DLP®, Digital Light
Processing™ and DMD are trademarks of Texas
Instruments, Inc

A brand of  **DELTA**