

[Click to Print This Page](#)



E-VISION 10000i 4K+ RGB



THE VISIONARIES CHOICE

E-Vision 10000i 4K+ RGB

10,000 ISO / 9,000 ANSI Lumens | Contrast Ratio: 3,000,000:1 (Dynamic Black) | Part Number: 124-360

Key Specifications:

Colour System:	Direct RGB Laser (no phosphor or color wheels)
Display Type:	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
DMD Specification:	1920 x 1200 pixels native display. (3840 x 2400 via 4-way pixel shift technology) Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	<p>RGB illumination</p> <ul style="list-style-type: none">The new E-Vision 10000i 4K+ RGB - an RGB illuminated 1-Chip projector. The single-chip E-Vision eliminates the artifacts and color separation commonly associated with projectors utilising a conventional colour wheel, while achieving 4K+ resolution <p>Video & Graphics Processing</p> <ul style="list-style-type: none">Nexus electronics platformHDMI 2.0DisplayPort 1.210-bit colour processing (30-bits per pixel) 1,073,741,824 coloursHue, Saturation and Gain colour management.24p and 1080p native display.

- HDR support
- Input source automatically detected
- Selectable Dynamic Black
- DICOM simulation mode
- Optics engine sealed to IP6X

Geometry Correction

- Vertical & Horizontal Keystone correction
- Four Corner adjustment
- Rotation -100 to +100 with +/- 0.25° per step
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled
- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

Edge Blending

- Correction for non-active pixels at the edge of the display.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

Source Compatibility

12G-SDI, Supports a high data transfer rate of up to 12 gigabits per second (Gbps), enabling the transmission of uncompressed 4K UHD (Ultra High Definition) video signals with a single connector

Graphics standards up to WUXGA 1920 x 1200 - 120Hz RB, Up to WQXGA 2560 x 1600 60Hz RB (DisplayPort)

Video standards including HDTV 1080p - 60Hz and 4K+ (3840 x 2400) 60Hz

Support for colour gamuts up to P3

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
HDMI 2.0b	HDMI	x 2

	<table border="1"> <tr> <td>Display Port 1.2</td> <td>DisplayPort</td> <td>x 2</td> </tr> <tr> <td>12G SDI IN</td> <td>BNC</td> <td>x 1</td> </tr> <tr> <td>12G SDI OUT</td> <td>BNC</td> <td>x 1</td> </tr> <tr> <td>HDBaseT</td> <td>8P8C "RJ45"</td> <td>x 1</td> </tr> </table>	Display Port 1.2	DisplayPort	x 2	12G SDI IN	BNC	x 1	12G SDI OUT	BNC	x 1	HDBaseT	8P8C "RJ45"	x 1																											
Display Port 1.2	DisplayPort	x 2																																						
12G SDI IN	BNC	x 1																																						
12G SDI OUT	BNC	x 1																																						
HDBaseT	8P8C "RJ45"	x 1																																						
	<table border="1"> <tr> <th colspan="3">Communication & Control</th> </tr> <tr> <th>Type</th> <th>Connector</th> <th>Qty</th> </tr> <tr> <td>3D Sync In</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>3D Sync Out (loop through)</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>3D Sync Out for IR</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>LAN / Art-Net</td> <td>EtherCON RJ45</td> <td>1</td> </tr> <tr> <td>HDBaseT/Ethernet/RS232/IR</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td>Serial In RS-232C</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Serial Out RS-232C</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Wired Remote In</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>Wired Remote Out</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>12V Trigger 12V 350mA</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>USB Power out 5V/2A</td> <td>USB Type A</td> <td>1</td> </tr> </table>	Communication & Control			Type	Connector	Qty	3D Sync In	BNC	1	3D Sync Out (loop through)	BNC	1	3D Sync Out for IR	BNC	1	LAN / Art-Net	EtherCON RJ45	1	HDBaseT/Ethernet/RS232/IR	RJ45	1	Serial In RS-232C	9-pin D-Sub	1	Serial Out RS-232C	9-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1	Wired Remote Out	3.5mm Stereo Jack	1	12V Trigger 12V 350mA	3.5mm Stereo Jack	1	USB Power out 5V/2A	USB Type A	1
Communication & Control																																								
Type	Connector	Qty																																						
3D Sync In	BNC	1																																						
3D Sync Out (loop through)	BNC	1																																						
3D Sync Out for IR	BNC	1																																						
LAN / Art-Net	EtherCON RJ45	1																																						
HDBaseT/Ethernet/RS232/IR	RJ45	1																																						
Serial In RS-232C	9-pin D-Sub	1																																						
Serial Out RS-232C	9-pin D-Sub	1																																						
Wired Remote In	3.5mm Stereo Jack	1																																						
Wired Remote Out	3.5mm Stereo Jack	1																																						
12V Trigger 12V 350mA	3.5mm Stereo Jack	1																																						
USB Power out 5V/2A	USB Type A	1																																						
3D Formats Supported	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential																																							
HDTV Formats Supported	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), 4K+ (3840 x 2400), DCI 4K (4096 x 2160)																																							
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, WQXGA																																							
Bandwidth																																								
Remote Control	Infrared/Wired Remote Control Unit																																							
Automation Control	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control																																							
Colour Temperature	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native)																																							
Operation																																								
illumination Type	RGB Laser																																							
Typical illumination Life	20,000 hours																																							
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.31 - 0.33:1 zoom</td> <td>124-318</td> <td>0.38 - 3.01m</td> <td>Vert: +/- 50% Hor: +/- 20%</td> </tr> <tr> <td>0.55 - 0.75:1 zoom</td> <td>124-319</td> <td>0.69 - 6.58m</td> <td>Vert: +/- 50% Hor: +/- 20%</td> </tr> </tbody> </table>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%	0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%																											
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																					
0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%																																					
0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%																																					

	<table border="1"> <tbody> <tr> <td>0.74 - 1.08:1 zoom</td> <td>124-320</td> <td>0.75 - 12.19m</td> <td>Vert: +/- 50% Hor: +/- 20%</td> </tr> <tr> <td>1.05 - 1.41:1 zoom</td> <td>124-321</td> <td>1.06 - 18.94m</td> <td>Vert: +/- 60% Hor: +/- 20%</td> </tr> <tr> <td>1.4 - 2.11:1 zoom</td> <td>124-322</td> <td>1.47 - 27.86m</td> <td>Vert: +/- 60% Hor: +/- 20%</td> </tr> <tr> <td>2.1 - 4.0:1 zoom</td> <td>124-323</td> <td>2.24 - 54.19m</td> <td>Vert: +/- 60% Hor: +/- 20%</td> </tr> <tr> <td>3.9 - 7.0:1 zoom</td> <td>124-446</td> <td>4.3 - 90.57m</td> <td>Vert: +/- 60% Hor: +/- 20%</td> </tr> </tbody> </table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>	0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%	1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%	1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%	2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%	3.9 - 7.0:1 zoom	124-446	4.3 - 90.57m	Vert: +/- 60% Hor: +/- 20%
0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%																		
1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%																		
1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%																		
2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%																		
3.9 - 7.0:1 zoom	124-446	4.3 - 90.57m	Vert: +/- 60% Hor: +/- 20%																		
Lens Mount	Centred lens for installation flexibility Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).																				
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm																				
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes																				
Power Requirements	100-240VAC 50/60Hz single phase 6.0A																				
Power Consumption	500W																				
Thermal Dissipation	1,706 BTU/hr																				
Fan Noise	Normal mode: 34 dBA typical Silence Mode: Max 32 dBA																				
Operating/Storage Temperature:	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)																				
Operating Humidity	90% (with maximum temperature of 35°C (95°F))																				
Weight	27 kg / 59.5 lbs																				
Dimensions	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch																				
Safety & EMC Regulations	TBD																				
Accessories	<table border="1"> <thead> <tr> <th>Accessory</th> <th>Part No.</th> </tr> </thead> <tbody> <tr> <td colspan="2"><i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i></td> </tr> </tbody> </table>	Accessory	Part No.	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>																	
Accessory	Part No.																				
<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>																					
Downloads																					
User Guide																					



DIGITAL PROJECTION, LTD



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



www.digitalprojection.com



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770



Specifications subject to change without notice.
©2024 Digital Projection. DLP®, Digital Light
Processing™ and DMD are trademarks of Texas
Instruments, Inc

A brand of 