

[Click to Print This Page](#)



## E-VISION 24000i WU



THE VISIONARIES CHOICE

## E-Vision 24000i WU

**23,750 ISO / 20,000 ANSI Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part Number: 124-359**

### Key Specifications:

<b>Colour System:</b>	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 4 Segment RGBY 2 x 7200rpm (120Hz)
<b>Display Type:</b>	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
<b>DMD Specification:</b>	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
<b>Aspect Ratio:</b>	16x10
<b>Fill Factor</b>	
<b>Key Features:</b>	<b>Video &amp; Graphics Processing</b> <ul style="list-style-type: none"><li>• Nexus electronics platform</li><li>• HDMI 2.0</li><li>• DisplayPort 1.2</li><li>• 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours</li><li>• Hue, Saturation and Gain colour management.</li><li>• 24p and 1080p native display.</li><li>• HDR support</li><li>• Input source automatically detected</li><li>• Selectable Dynamic Black</li><li>• Synchronisation of active glasses or polarising switcher.</li></ul>

- DICOM simulation mode
- Optics engine sealed to IP6X

### Geometry Correction

- Vertical & Horizontal Keystone correction
- Four Corner adjustment
- Rotation -100 to +100 with +/- 0.25° per step
- Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled
- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

### Edge Blending

- Correction for non-active pixels at the edge of the display.

### HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

### Colour Processing

- Powerful seven point colour correction for accurate colour matching.

### Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

### Source Compatibility

Graphics standards up to WQXGA 2560 x 1600 60 Hz RB (DisplayPort).

Display Support for 3840 x 2160 (4K-UHD) up to 60Hz and 4096 x 2160 (4K) up to 60Hz.

### Inputs/Outputs

Video & Computer		
Type	Connector	Qty
HDMI 2.0 (HDCP compatible)	HDMI	2
DisplayPort 1.2	DisplayPort	2
HDBaseT	8P8C "RJ45"	1
3G-SDI in	BNC	1
3G-SDI out	BNC	1
Communication & Control		
Type	Connector	Qty
3D Sync In	BNC	1
3D Sync Out (loop through)	BNC	1

	<table border="1"> <tr> <td>3D Sync Out for IR</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>LAN / Art-Net</td> <td>EtherCON RJ45</td> <td>1</td> </tr> <tr> <td>HDBaseT/Ethernet/RS232/IR</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td>Serial In RS-232C</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Serial Out RS-232C</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Wired Remote In</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>Wired Remote Out</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>12V Trigger 12V 350mA</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>USB Power out 5V/2A</td> <td>USB Type A</td> <td>1</td> </tr> </table>	3D Sync Out for IR	BNC	1	LAN / Art-Net	EtherCON RJ45	1	HDBaseT/Ethernet/RS232/IR	RJ45	1	Serial In RS-232C	9-pin D-Sub	1	Serial Out RS-232C	9-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1	Wired Remote Out	3.5mm Stereo Jack	1	12V Trigger 12V 350mA	3.5mm Stereo Jack	1	USB Power out 5V/2A	USB Type A	1	
3D Sync Out for IR	BNC	1																											
LAN / Art-Net	EtherCON RJ45	1																											
HDBaseT/Ethernet/RS232/IR	RJ45	1																											
Serial In RS-232C	9-pin D-Sub	1																											
Serial Out RS-232C	9-pin D-Sub	1																											
Wired Remote In	3.5mm Stereo Jack	1																											
Wired Remote Out	3.5mm Stereo Jack	1																											
12V Trigger 12V 350mA	3.5mm Stereo Jack	1																											
USB Power out 5V/2A	USB Type A	1																											
<b>3D Formats Supported</b>	Off Auto Side by Side Top and Bottom Dual Pipe Frame Sequential																												
<b>HDTV Formats Supported</b>	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), Display Support for 3840 x 2160 (4K-UHD) up to 60Hz and 4096 x 2160 (4K) up to 60Hz																												
<b>Computer Compatibility</b>	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA up to 60hz RB, Mac																												
<b>Bandwidth</b>																													
<b>Remote Control</b>	Infrared Remote Control Unit																												
<b>Automation Control</b>	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control																												
<b>Colour Temperature</b>	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native )																												
<b>Operation</b>																													
<b>illumination Type</b>	Laser Phosphor. ECO mode support (80% Brightness)																												
<b>Typical illumination Life</b>	20,000 hours																												
<b>Lenses</b>	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.31 - 0.33:1 zoom</td> <td>124-318</td> <td>0.38 - 3.01m</td> <td>Vert: +/- 50% Hor: +/- 20%</td> </tr> <tr> <td>0.55 - 0.75:1 zoom</td> <td>124-319</td> <td>0.69 - 6.58m</td> <td>Vert: +/- 50% Hor: +/- 20%</td> </tr> <tr> <td>0.74 - 1.08:1 zoom</td> <td>124-320</td> <td>0.75 - 12.19m</td> <td>Vert: +/- 50% Hor: +/- 20%</td> </tr> <tr> <td>1.05 - 1.41:1 zoom</td> <td>124-321</td> <td>1.06 - 18.94m</td> <td>Vert: +/- 60% Hor: +/- 20%</td> </tr> <tr> <td>1.4 - 2.11:1 zoom</td> <td>124-322</td> <td>1.47 - 27.86m</td> <td>Vert: +/- 60% Hor: +/- 20%</td> </tr> <tr> <td>2.1 - 4.0:1 zoom</td> <td>124-323</td> <td>2.24 - 54.19m</td> <td>Vert: +/- 60%</td> </tr> </tbody> </table>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%	0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%	0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%	1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%	1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%	2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60%
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																										
0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%																										
0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%																										
0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%																										
1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%																										
1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%																										
2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60%																										

			Hor: +/- 20%
	3.0 - 4.52:1 zoom	112-503	2.53 - 47.2m Vert: +/- 45% Hor: +/- 10%
	4.46-6.94:1 zoom	112-504	3.71 - 76.7m Vert: +/- 45% Hor: +/- 10%
	* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,		
<b>Lens Mount</b>	Centred lens for installation flexibility Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).		
<b>Mechanical Mounting</b>	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm		
<b>Orientation</b>	<b>Table Top or Inverted:</b> Yes <b>Pointing Up:</b> Yes <b>Pointing Down:</b> Yes <b>Roll (Portrait):</b> Yes		
<b>Power Requirements</b>	110-240 VAC 11.0A 50/60Hz		
<b>Power Consumption</b>	at 110VAC - typical 1100 W, max 1200 W in Normal mode at 110VAC - typical 900 W, max 1000 W in High Altitude mode at 220VAC - typical 1300 W, max 1400 W in Normal mode at 220VAC - typical 900 W, max 1000 W in Eco mode at 220VAC - typical 900 W, max 1000 W in High Altitude mode		
<b>Thermal Dissipation</b>	at 110 VAC: typical 3576 BTU/hr, max 4097 BTU/hr in Normal mode at 110 VAC: typical 3073 BTU/hr, max 3415 BTU/hr in High Altitude mode at 220 VAC: typical 4438 BTU/hr, max 4780 BTU/hr in Normal mode at 220 VAC: typical 3073 BTU/hr, max 3415 BTU/hr in ECO mode at 220 VAC: typical 3073 BTU/hr, max 3415 BTU/hr in High Altitude mode		
<b>Fan Noise</b>	Typical 44dB, max 46dB in Normal mode Typical 39dB, max 41dB in ECO mode		
<b>Operating/Storage Temperature:</b>	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)		
<b>Operating Humidity</b>	90% (with maximum temperature of 35°C (95°F))		
<b>Weight</b>	30kg (without lens) kg / 66.1lb (without lens) lbs		
<b>Dimensions</b>	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch		
<b>Safety &amp; EMC Regulations</b>	cTUVus, CB report, CCC (China), CECP (China Energy Conservation Program), China RoHS, FCC part 15 Class A, FDA 21 CFR part 1040 (Except with respect to those characteristics authorised by Variance Number 2021-V-0192, CE (European Economic Area), UKCA (United Kingdom), KC (Korea), BSMI (Taiwan), RCM (Australia), IEC 60825-1 : 2014 - Class 1 Laser Product, IEC EN 62471-5:2015 - Risk Group 2 This projector may become Risk Group 3 when an interchangeable lens with a throw ratio of greater than 2.12:1 is installed Such combinations of projector and lens are intended for professional use only and are not intended for consumer use.		
<b>Accessories</b>			

	Accessory	Part No.
	*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.	
Downloads		
User Guide		



**DIGITAL PROJECTION, LTD**



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



[www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, INC**



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



[www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, CHINA**



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,  
PR China



T: +86.10.58239771 | F: +86 10 58239770



Specifications subject to change without notice.  
©2024 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

A brand of 