

[Click to Print This Page](#)



E-VISION LASER 6110 DIGITAL PROJECTOR

THE VISIONARIES CHOICE




E-Vision 6110 WU (Preliminary)

6,100 ISO / 5,500 ANSI Lumens | Contrast Ratio: 2,200:1 Native, 20,000:1 Dynamic, 500,000:1 (Advanced Black) | Part Number: 123-844

Key Specifications:

Colour System:	Laser Phosphor
Display Type:	1 x 0.67" DarkChip™ DMD™
DMD Specification:	1920 x 1200 pixels native resolution. Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	
Key Features:	<p>Video & Graphics Processing</p> <ul style="list-style-type: none">• HDMI 1.4a mandatory compliance for Side by Side, Frame Packing, Frame Sequential and TopBottom 3D Formats.• Synchronisation of active glasses or polarising switcher.• DICOM simulation mode <p>Geometry Correction</p> <ul style="list-style-type: none">• Vertical & Horizontal Keystone correction• Four Corner adjustment• Selectable aspect ratios: Fill, 4:3, 16:9, Letter Box, Native, 2.35:1• Digital Zoom +10 / -10


	HDBaseT Interface <ul style="list-style-type: none"> Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable. Allows the projector to be placed up to 100m from the source with low cost cabling. HDBaseT® Includes Audio, Ethernet 100BaseT and RS232/IR control. Colour Processing <ul style="list-style-type: none"> Phosphor wheel: 3 Segment GBY 2 x 7200rpm Colour wheel: 4 Segment RGBW 2 x 7200rpm 10-bit colour processing (30-bits per pixel) Powerful seven point colour correction for accurate colour matching. Source Compatibility <ul style="list-style-type: none"> Graphics standards up to 1920 x 1200 resolution at 60Hz 		
Inputs/Outputs	Video & Computer		
	Type	Connector	Qty
	HDMI 1.4a	HDMI	3
	HDBaseT-(LAN/HDBaseT)	8P8C "RJ45"	
	VGA / Analog RGB	D-Sub	1
	VGA Monitor out	D-Sub	1
	Composite Video	RCA	1
			1
	Microphone In	3.5mm Jack	
	Audio L/R In	3.5mm Jack	1
	Audio L/R In	1xRCA pair	1
	Audio L/R Out	3.5mm Jack	1
			1
	Communication & Control		
	Type	Connector	Qty
	3D Sync Out	3-pin DIN	1
	LAN	8P8C "RJ45"	1
	HDBaseT with Ethernet \	8P8C "RJ45"	1
	RS232 \IR control	9-pin D-Sub	1
	Serial RS-232C (In/Out)	USB Type B	1
	Service USB	USB Type A	1
	USB Power out 5V/1.5A		
3D Formats Supported	Frame Packing Frame Sequential Side By Side (half) Top and Bottom		
HDTV Formats Supported	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N), SECAM (B,D,G,K,K1,L)		
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac		
Bandwidth			

Remote Control	IR remote control										
Automation Control	LAN RS-232 Alert Mail for Projector LAN Control-Crestron® Roomview™-Connected LAN Control-Crestron® eControl LAN control - Extron® LAN Control-PJ Link compatible LAN Control-AMX® SSDP LAN to RS232 (RS232 by Telnet) Concurrence Control for RS232/LAN PJ Link (Class 1)										
Colour Temperature	Warm / Normal / Cold										
Operation											
illumination Type	Laser Light Source										
Typical illumination Life	20,000 hours										
Lenses	<table border="1"> <thead> <tr> <th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr> </thead> <tbody> <tr> <td>0.5:1 (fixed)</td><td>N/A</td><td>0.76m - 1.35m (optical range) 0.60m - 3.5m (Mechanical range)</td><td>Vert: Fixed Offset 0.6 (U) frame</td></tr> </tbody> </table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.5:1 (fixed)	N/A	0.76m - 1.35m (optical range) 0.60m - 3.5m (Mechanical range)	Vert: Fixed Offset 0.6 (U) frame
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)								
0.5:1 (fixed)	N/A	0.76m - 1.35m (optical range) 0.60m - 3.5m (Mechanical range)	Vert: Fixed Offset 0.6 (U) frame								
Lens Mount	Manual focus										
Mechanical Mounting	Front/Rear Front/Rear Ceiling Two adjustable front feet, 10° (43mm) Ceiling Mount compatible chassis with 7 off M4 mounting holes Kensington® Security Slot										
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes										
Power Requirements	100-240VAC 50/60Hz single phase										
Power Consumption	515W @ 230VAC (100% Normal mode) Maximum 530W @ 100VAC (100% Normal mode) Maximum										
Thermal Dissipation	1757 BTU/Hour @ 230VAC (100% Normal mode) 1808 BTU/Hour @ 100VAC (100% Normal mode)										
Fan Noise	Normal Mode Typ: 39 dBA										
Operating/Storage Temperature:	Operating: 0° to 40°C (32F to 104F) Storage: -20° to 60°C (-4F to 140F)										
Operating Humidity	10 to 85% non-condensing										
Weight	12 kg / 26.45 lbs										

Dimensions	L: 43.71 cm W: 36.0 cm H: 17.83 cm L: 17.2 in W: 14.17 in H: 7.02 in	
Safety & EMC Regulations	UL / cUL (USA/Canada), CB, CCC (China), FCC Class B (USA), FDA, CE (European Economic Area), RCM (Australia), Others TBD	
Accessories	Accessory	Part No.
	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>	
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings	
User Guide	User Guides Laser Risk Group Document	



DIGITAL PROJECTION, LTD

 Unit 3, Aniseed Park, Broadgate,
Oldham, UK OL9 9XA

 T: +44 (0)161 947 3300
 www.digitalprojection.com




DIGITAL PROJECTION, INC


 55 Chastain Road, Suite 115 Kennesaw, GA.
30144

 T: 770.420.1350 | F: 770.420.1360
 www.digitalprojection.com



DIGITAL PROJECTION, CHINA

 Rm A2301, Shaoyaoju 101 North Lane, Shi Ao
International Center, Chaoyang District, Beijing 100029,
PR China

 T: +86.10.58239771 | F: +86 10 58239770



Specifications subject to change without notice.
©2024 Digital Projection. DLP®, Digital Light
Processing™ and DMD are trademarks of Texas
Instruments, Inc

