



Satellite Modular Laser System Specification (Preliminary)

Satellite MLS is a (r)evolution in projection technology.

Totally configurable to overcome traditional installation challenges.

Simple building blocks for complex applications.



Satellite Insight MLS 4K HFR 360

(Preliminary Specification)

MultiView - up to 3 stereo simultaneous views



10,000 to 40,000 Lumens | Contrast Ratio: 2,000:1

Key Features:

Satellite Insight Head

Native 4K Resolution (4096 x 2160)
 High frame rate up to 360fps
 Separate Head - compact, lightweight & low noise
 Sealed Optics
 Near Maintenance free
 3D Capable

Modular Light Source

RGB Modular Light source
 Near BT2020 colour space
 Rack mountable • Fully Interlocked
 Interconnection - Satellite Link Cable available in various lengths
 Combines 1,2,3,4 Modular Light Sources

Key Specifications:

Colour System:	3-chip DLP®																								
Display Type:	3 x 1.38" DarkChip™ DMD™																								
DMD Specification:	4096 x 2160 pixels native. Fast transit pixels for smooth greyscale and improved contrast.																								
Aspect Ratio:	1.90:1																								
Fill Factor	87%																								
Video & Graphics processing	Up to 6 x 60 fps 4096 x 2160 pixels sequential input via single DisplayPort input. Dual Flash Processing capability. Dark Time insertion capability. Smear reduction for 2D displays. Synchronisation of active glasses or polarising switcher. Low latency processing.																								
Colour adjustments	Up to 12 bits per colour (RGB) processing (depending on source and input type). Degamma table maps input to 16 bit palette (R, G & B) for display. Degamma selection from a list of parametric curves. Individual R, G & B lift and gain. Black and White level adjustment via Brightness & Contrast control.																								
ColorMax™	Accurate matching of projectors in tiled or blended applications. User selection and storage of primary and secondary user defined color targets up to 7 points.																								
Control	On-board touch-panel control. Remote control - IR or cable. Network control via RJ45. Tablet and smart phone control via served web page. PC control application.																								
Mounting	Head mounting Fixing points on Top/Bottom and sides. Additional front fixing for third party attachments i.e optical blenders. MLS Mounting 19" 3U rack mounting																								
Lens Features	Robust lens mount with memorised position, zoom and focus. Extensive lens shift encompassing all lens capabilities. High quality sharp lenses designed for 4K performance with wide focal ranges.																								
Source Compatibility	Graphics standards up to 4096 x 2160 at 60 fps via each DisplayPort. 60 fps via HDMI. Higher input frame rates supported at 2K resolution.																								
Inputs/Outputs	<table border="1"> <thead> <tr> <th colspan="3">Video & Computer</th> <th colspan="3">Communication & Control</th> </tr> </thead> <tbody> <tr> <td>DisplayPort 1.2</td> <td>DisplayPort</td> <td>6</td> <td>3D Sync in/out</td> <td>BNC</td> <td>2</td> </tr> <tr> <td>HDMI</td> <td>HDMI</td> <td>2</td> <td>LAN</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td></td> <td>Wired remote</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> </tbody> </table>	Video & Computer			Communication & Control			DisplayPort 1.2	DisplayPort	6	3D Sync in/out	BNC	2	HDMI	HDMI	2	LAN	RJ45	1				Wired remote	3.5mm Stereo Jack	1
Video & Computer			Communication & Control																						
DisplayPort 1.2	DisplayPort	6	3D Sync in/out	BNC	2																				
HDMI	HDMI	2	LAN	RJ45	1																				
			Wired remote	3.5mm Stereo Jack	1																				
3D Formats Supported	Dual Pipe & Frame Sequential. Frame Packed, Top-Bottom via HDMI																								

Formats Supported	4096 x 2160p (24, 25, 29.97, 30, 50, 59.94, 60 Hz) (Up to 120 Hz via Dual Pipe, or up to 360 Hz via 6 channels) 3840 x 2160p (24, 25, 29.97, 30, 50, 59.94, 60 Hz) (Up to 120 Hz via Dual Pipe) 1080p (24, 25, 29.97, 30, 50, 59.94, 60 Hz) (Up to 120 Hz)																														
Computer Compatibility	Up to 4096 x 2160																														
Projector Head Control	IR & Wired remote control & On-Board touch-panel with OSD																														
Automation Control	LAN.																														
Colour Temperature	User selectable from 3300 to 10000K																														
illumination Type	RGB Laser Light Source																														
Typical illumination Life	30,000 Hours																														
Lenses	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.93:1 fixed</td> <td>117-310</td> <td>Vert: 0.21 (U) 0.21 (D), Hor: 0.08 (L) 0.08 (R)</td> </tr> <tr> <td>1.13 - 1.72:1</td> <td>115-627</td> <td>Vert: 0.34 (U) 0.19 (D), Hor: 0.08 (L) 0.10 (R)</td> </tr> <tr> <td>1.65 - 2.60:1</td> <td>115-630</td> <td>Vert: 0.40 (U) 0.20 (D), Hor: 0.13 (L) 0.13 (R)</td> </tr> <tr> <td>2.53 - 4.98:1</td> <td>115-632</td> <td>Vert: 0.37 (U) 0.20 (D), Hor: 0.13 (L) 0.13 (R)</td> </tr> <tr> <td colspan="3">At 4K-UHD</td> </tr> <tr> <td>0.99:1 fixed</td> <td>117-310</td> <td>Vert: 0.27 (U) 0.20 (D), Hor: 0.10 (L) 0.11 (R)</td> </tr> <tr> <td>1.21 - 1.83:1</td> <td>115-627</td> <td>Vert: 0.40 (U) 0.20 (D), Hor: 0.08 (L) 0.14 (R)</td> </tr> <tr> <td>1.76 - 2.77:1</td> <td>115-630</td> <td>Vert: 0.45 (U) 0.20 (D), Hor: 0.13 (L) 0.17 (R)</td> </tr> <tr> <td>2.70 - 5.31:1</td> <td>115-632</td> <td>Vert: 0.42 (U) 0.20 (D), Hor: 0.13 (L) 0.17 (R)</td> </tr> </tbody> </table>	Lens	Part No.	Lens Shift (Frame)	0.93:1 fixed	117-310	Vert: 0.21 (U) 0.21 (D), Hor: 0.08 (L) 0.08 (R)	1.13 - 1.72:1	115-627	Vert: 0.34 (U) 0.19 (D), Hor: 0.08 (L) 0.10 (R)	1.65 - 2.60:1	115-630	Vert: 0.40 (U) 0.20 (D), Hor: 0.13 (L) 0.13 (R)	2.53 - 4.98:1	115-632	Vert: 0.37 (U) 0.20 (D), Hor: 0.13 (L) 0.13 (R)	At 4K-UHD			0.99:1 fixed	117-310	Vert: 0.27 (U) 0.20 (D), Hor: 0.10 (L) 0.11 (R)	1.21 - 1.83:1	115-627	Vert: 0.40 (U) 0.20 (D), Hor: 0.08 (L) 0.14 (R)	1.76 - 2.77:1	115-630	Vert: 0.45 (U) 0.20 (D), Hor: 0.13 (L) 0.17 (R)	2.70 - 5.31:1	115-632	Vert: 0.42 (U) 0.20 (D), Hor: 0.13 (L) 0.17 (R)
Lens	Part No.	Lens Shift (Frame)																													
0.93:1 fixed	117-310	Vert: 0.21 (U) 0.21 (D), Hor: 0.08 (L) 0.08 (R)																													
1.13 - 1.72:1	115-627	Vert: 0.34 (U) 0.19 (D), Hor: 0.08 (L) 0.10 (R)																													
1.65 - 2.60:1	115-630	Vert: 0.40 (U) 0.20 (D), Hor: 0.13 (L) 0.13 (R)																													
2.53 - 4.98:1	115-632	Vert: 0.37 (U) 0.20 (D), Hor: 0.13 (L) 0.13 (R)																													
At 4K-UHD																															
0.99:1 fixed	117-310	Vert: 0.27 (U) 0.20 (D), Hor: 0.10 (L) 0.11 (R)																													
1.21 - 1.83:1	115-627	Vert: 0.40 (U) 0.20 (D), Hor: 0.08 (L) 0.14 (R)																													
1.76 - 2.77:1	115-630	Vert: 0.45 (U) 0.20 (D), Hor: 0.13 (L) 0.17 (R)																													
2.70 - 5.31:1	115-632	Vert: 0.42 (U) 0.20 (D), Hor: 0.13 (L) 0.17 (R)																													
Lens Mount	Motorised shift, zoom and focus. Intelligent Lens Memory with user-definable preset positions.																														
Mechanical Mounting	Front/Rear Table. Front/Rear Ceiling . Adjustable Front/Rear Feet.																														
Orientation	Table Top or Inverted:. Pointing Up. Pointing Down. Roll (Portrait)																														
Power Requirements	Head, MLS & SCM 100 - 240VAC 50/60Hz single phase																														
Power Consumption	Head 250W. Single MLS 1000W SCM 100W																														
Thermal Dissipation	Head with 10K Lumens 1200 BTU/Hr with 40K Lumens 2220 BTU/hr Single MLS 3412 BTU/hr																														
Fan Noise	Head <40 dBA MLS <43 dBA SCM 30 dBA																														
Operating/Storage Temperature	Operating: 0 to 35C (32 to 95F) Storage: -10 to 50C (14 to 122F)																														
Operating Humidity	20 to 80% non-condensing																														
Weight	Head: 46 kg /101.5 lbs MLS: 16.5 kg / 37 lbs SCM: 7 kg / 15.5 lbs																														
Dimensions	Head H: 47 cm W: 43 cm L: 45 cm H: 18.5 in W: 16.9 in L: 17.7 in Modular Light Source (MLS) 19" 3U rack unit 50cm / 19.6" deep Satellite Control Module (SCM) 19" 4U rack unit 40cm / 15.8" deep																														
Systems	Satellite Insight 10,000 4K HFR 360 with 10m Satellite Link Cable - 121-372 Satellite Insight 20,000 4K HFR 360 with 10m Satellite Link Cable - 121-373 Satellite Insight 30,000 4K HFR 360 with 10m Satellite Link Cable - 121-374 Satellite Insight 40,000 4K HFR 360 with 10m Satellite Link Cable - 121-375																														



INSIGHT Satellite Head



Modular Light Source (MLS)



Satellite Link Cable (SLC)



System Control Module (SCM)

DIGITAL PROJECTION, LTD GREENSIDE WAY,
MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 |
www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN
ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 } F: 770.420.1360 |
www.digitalprojection.com

DIGITAL PROJECTION, CHINA Rm
A2301,Shaoyaoju 101 North Lane,Shi Ao
International Center,Chaoyang District,Bei-
jing 100029,PR China. T: +86.10.58239771 |
F: +86 10 58239770



A Delta Associate Company

Document ref: 121-895B

Laser class Statement: Class 1 RG3 Laser Product. No direct exposure to the beam shall be permitted, RG3 IEC 62471-5:2015. Operators shall control access to the beam within the hazard distance or install the product at a height that will prevent exposure of the spectator's eyes within the hazard distance

Specifications subject to change without notice.

©2022 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc